

# Behavior of Reinforced Concrete Frame with Masonry Infill Wall Subjected to Vertical Load

Hadi Baghi<sup>1</sup>, André Oliveira<sup>2</sup>, Eduardo Cavaco<sup>3</sup>, Luís Neves<sup>4</sup>, Eduardo Júlio<sup>5</sup>

## Abstract:

The effectiveness of masonry infill wall on behavior of a Reinforced Concrete (RC) frame subjected to a column failure is studied experimentally. For this reason, one full scale RC frame designed according to Eurocode is statically tested to investigate the behavior of the frame with and without masonry infill wall. The obtained results show that infill wall can significantly increase the load carrying capacity of RC frame and thus serve as an important robustness reserve in the case of unpredictable extreme events (i.e. local impact, blast or earthquake). A photogrammetry analysis is carried out to study the behavior of the structure. Results give valuable information about the alternative load path, transfer of the applied load to the column and beams, and interaction forces between RC frame and infill wall. At the end, the experimental program is simulated by the OpenSees software to study the behavior of the frame. After having demonstrated that this model can predict the load deflection with good accuracy, a parametric study is conducted to evaluate the effect of the percentage of longitudinal reinforcement ratio of beams and columns on the load carrying capacity of the infilled RC frame.

**Keywords:** Robustness, Reinforced Concrete Frame, Infill walls, Photogrammetry, OpenSees.

---

<sup>1</sup> Post Doc, College of Engineering, Wayne State University, Detroit, Michigan, U.S. (corresponding author) e-mail: hadibaghi@gmail.com.

<sup>2</sup> Researcher, Faculdade de Ciências e Tecnologia, Universidade NOVA de Lisboa, Portugal, e-mail: oliveirahoalbo@gmail.com.

<sup>3</sup> Assistant Professor, CERIS, Instituto Superior Técnico, Universidade de Lisboa, Portugal, e-mail: e.cavaco@fct.unl.pt.

<sup>4</sup> Lecturer, Nottingham Transportation Engineering Centre (NTEC), Dept. of Civil Engineering, University of Nottingham, Nottingham, United Kingdom, e-mail: Luis.Neves@nottingham.ac.uk.

<sup>5</sup> Professor, CERIS, Instituto Superior Técnico, Universidade de Lisboa, Portugal, e-mail: eduardo.julio@tecnico.ulisboa.pt.

22 **Introduction:**

23 Progressive collapse means failure of a primary structural element that can resulting in the failure  
24 of adjoining structural elements, which in turn causes further structural failure [1]. Progressive  
25 collapse of multistory buildings can occur after local failure of a key structural member, typically  
26 originated by extreme unforeseen events, such as: earthquake, different types of natural disasters,  
27 man-caused accidents, and terrorist attacks. In Ronan Point, London [2], a gas explosion on the  
28 18<sup>th</sup> floor of a residential building blew out a wall element causing a progressive collapse of the  
29 building. In the Bad Reichnhall arena, Germany [2], due to a design error and undetected  
30 deterioration, a progressive collapse occurred under snow load, and led to the total collapse of  
31 the roof of the structure. These are clearly some examples of non-robust structures and the  
32 observed types of failure that may be seen as the result of the incapacity of the structures to  
33 develop alternative load paths after local damage of a member [3].

34 To avoid disproportionate failure, robustness must be ensured, i.e. the structure must develop  
35 alternative load paths after loss of a key-member. For instance, after sudden failure of a column,  
36 the connecting beams and infill panels must be able to transfer the redistributed loads to the  
37 adjacent columns [4]. This scenario highlights the importance of robustness. Robustness has  
38 been recognized as a desirable property of structural systems which mitigates their susceptibility  
39 of progressive disproportionate collapse [5]. In general, robustness is defined as the insensitivity  
40 of a structure to local failure. In a robust structure, no damage disproportionate to the initial  
41 failure will occur. Thus, an appropriate assessment of the structural behavior requires accounting  
42 for alternative load bearing scenarios that contribute to the overall resistance. Among the  
43 fundamental mechanisms of arrest, shear deformation of infill panels can provide significant  
44 enhancement of the resistance against collapse in frame RC structures [4].

45 The influence of the masonry infill panels is not generally considered in the design process of  
46 RC frames subjected to lateral loads, due to early brittle failure and consequently formation of  
47 soft-story mechanism and column shear failure. In reality, masonry walls are often arranged non-  
48 uniformly in different floors for functional reasons that cause the RC buildings have vertical  
49 irregularity, such as stiffness irregularity (soft story), strength irregularity (weak story), mass  
50 irregularity, and short-column effects. However, it is generally accepted that these elements have  
51 a significant influence on the structural behavior. They increase initial stiffness and decrease the  
52 natural period of the frame, which might be beneficial depending on the frequency of earthquake  
53 motion [6].

54 Shan et al. [7] studied experimentally the progressive collapse of a two-story four-bay RC frame  
55 with and without infill wall. The test results showed that the infill walls can provide alternative  
56 load paths for transferring the loads originally only supported by the beams, and thus, improve  
57 the collapse resistance capacity of the RC frame.

58 Tsai and Huang [8, 9] studied the progressive collapse of RC frames numerically and showed the  
59 effect of infill walls on the structure's resistance capacities against progressive collapse. The  
60 results showed that the progressive collapse depends on the dimensions as well as the locations  
61 of infill wall. However, infill walls have slightly influence on the structure's collapse resistance  
62 capacity because, infill walls have a brittle behavior and with a small deformation whereas  
63 collapse of structures is involving with a large deformation [7].

64 Tiago and Julio [10] described a case-study of a 12 stories residential building that experienced a  
65 landslide during the rainy season which destroyed three perimeter columns at the basement level  
66 and that, nonetheless, did not collapse because masonry infill walls created an alternative load  
67 path and transferred load failed columns to adjacent columns. Cachado et al. [2] performed a

68 numerical simulation on the mentioned building. Authors concluded that regardless of the low  
69 mechanical resistance of masonry infill wall elements, compared with other structural elements,  
70 their contribution for the global behavior of the damaged structure is essential.

71 In a research conducted by Pujol et al. [11], the influence of masonry infill walls in the  
72 mitigation of progressive collapse of a RC structure was investigated by conducting an  
73 experimental program composed of a full-scale three-story flat-plate structure that was  
74 strengthened with infill brick walls. Results have shown that continuous masonry infill walls can  
75 contribute positively to reduce the vulnerability of the RC structures. These walls were effective  
76 in terms of increasing the strength (by 100%) and stiffness (by 500%) compared to the reference  
77 frame without masonry infill wall.

78 The behavior of Hotel San Diego, a six-story reinforced concrete infilled-frame structure that  
79 two adjacent columns simultaneously were removed using explosives, was studied by Sasani  
80 [12]. The structure resisted progressive collapse with a measured maximum vertical  
81 displacement of 6.4 mm above the removed columns. Reaction of transverse and longitudinal  
82 frames with contribution of infill walls were identified as the principal mechanism for  
83 redistribution of the loads in the structure.

84 The purpose of this study is to experimentally evaluate the behavior of a full-scale RC frame  
85 designed according to Eurocode 2 (EC2) [13] and Eurocode 8 (EC 8) [14], featured without and  
86 with the infill walls in the case of loss of a supporting column and to study the role that the infill  
87 wall played in the stiffness of the RC frame. The frame is filled by typical double ceramic brick  
88 wall. In this study the dynamic aspects of the column failure and the resulting frame response are  
89 not studied, and attention is just given to the quasi-static loading behavior of the RC frame. The  
90 experimental program consisted of one full scale RC frame subjected to vertical load as column

91 failure and tested in three phases: i) isolated RC frame tested in elastic regime; ii) RC frame with  
92 masonry infill wall tested up to failure of the wall; and iii) isolated RC frame after infill wall  
93 removal tested up to failure. The experimental program is detailed, and the obtained results are  
94 presented and discussed.

95 Following the experimental research, a numerical simulation was carried out using the OpenSees  
96 software [15]. The values of the parameters that define constitutive models used in numerical  
97 simulation were calibrated by simulating the tested frame, considering the properties obtained in  
98 the experimental programs for the characterization of the relevant properties of the used  
99 materials, and the suggestion of EC2 [13]. After having been demonstrated that the model is  
100 capable of simulate the behavior of the tested frame with high accuracy, a parametric study was  
101 carried out to study the influence of the percentage of longitudinal reinforcement ratio in beams  
102 and columns on the load carrying capacity of the infilled frame.

103

#### 104 **Experimental Program:**

105 3D frame is used to address three dimensional effects such as contribution of slabs, while 2D  
106 frame may give conservative results if these results are not accounted for [7]. However, 2D  
107 frame is recognize accurate to study the behavior of infill walls in term of progressive collapse.  
108 The experimental program was composed of one real scale one-bay, one-story reinforced  
109 concrete frame (5000 mm×2550 mm<sup>2</sup>, center to center), designed according to EC2 and EC8 [13,  
110 14]. According to EC8 [14], the frame was designed to have strong columns and weak beams.  
111 Al-Chaar and Lamb [16] model was used to estimate the influence of the infill wall on the RC  
112 frame and then reinforcement was oversized to allow a single frame to be tested in three  
113 different phases without experiencing significant damage. Dimensions and reinforcement details

114 of the frame are presented in Fig. 1. To allow in-plane deformation, the out of plane deformation  
115 was restrained at the upper beam level. The right-hand column base was fixed in both directions  
116 (horizontal and vertical), to present the lower floor column and the horizontal elements at the  
117 adjacent span. A vertical constant load of 220 kN was applied to represent the upper floor  
118 column axial force. This load was applied by pre-stressing of two vertical steel bars as shown in  
119 Fig. 1. Longitudinal reinforcement ratio in columns and beams was 2.7% and 0.96%,  
120 respectively, whereas transverse reinforcement ratio was 0.88% and 0.44%. The left side column  
121 bottom was not presented in structural design to simulate the scenario of removal column from  
122 system.

123 The experimental program was divided in three main phases:

124 Phase 1: Elastic regime (F-Re) (Fig. 1b), to understand the behavior of the frame without  
125 masonry infill wall. As mentioned before, the frame was oversized, then no plastic  
126 strains were expected to be reached in the longitudinal reinforcement.

127 Phase 2: In this phase the frame was filled by typical double ceramic brick wall (T-Tr)  
128 (Fig. 2) and was pushed up to failure of the wall. The ceramic bricks used in the two wall  
129 panels had a dimension of  $300 \times 200 \times 150 \text{ mm}^3$  and  $300 \times 200 \times 110 \text{ mm}^3$ . An air gap of 40  
130 mm was left between the wall panels to improve thermal performance. Again, due to  
131 increased stiffness provided by the masonry wall, no plastic strains were expected to be  
132 reached in the longitudinal reinforcement of RC frame.

133 Phase 3: in this phase the infilled wall was removed, and the bare frame was pushed up to  
134 failure (F-B).

135

136

137 *Material Properties*

138 The shear strength of masonry wall units was assessed according to EN 1052-3 [17]. As shown  
139 in Fig. 3a, specimens composed of three bricks and two mortar interfaces were tested under a 3-  
140 point load test setup. Supports were placed under the lateral bricks, whereas the load was applied  
141 to the central brick. To measure vertical displacements, a set of three Linear Variable Differential  
142 Transducer (LVDT) was used, as shown in Fig. 3b. The relative displacements of lateral bricks  
143 to the central brick were measured using LVDTs 1 and 2, while LVDT 3 was used to measure  
144 the absolute displacement of the central brick. The shear strength of each specimen was  
145 determined according to Eq. (1):

$$f_v = \frac{F_{\max}}{2A} \quad (1)$$

146 where  $F_{\max}$  is the maximum applied load and  $A$  is the effective normal area of the specimen.

147 The results of shear strength are presented in Table 1. According to the results, the shear strength  
148 of masonry wall is highly dependent on the mortar interface strength, because all the three  
149 samples failed at mortar interface.

150 Masonry compressive strength was executed on prismatic specimens composed by three bricks  
151 and two mortar interfaces, as shown in Figs. 3c and 3d. Each specimen was monitored with one  
152 vertical LVDT to measure modulus of elasticity. A 300 kN load cell was used to measure testing  
153 force. In the first stage, five load-unload cycles were applied (Fig. 4). As shown in this figure,  
154 the first two cycles were driven up to a maximum load corresponding to  $0.1f_k$ , and the  
155 remaining three cycles were driven up to  $0.2f_k$ . For each cycle, the maximum load was kept  
156 constant during 30s. Then, the load was increased up to failure of the specimens. During this last

157 stage, a vertical displacement was imposed at a rate of 0.01 mm/s. The compressive strength,  $f_c$ ,  
158 of each specimen, was computed by the following equation [18]:

$$f_c = \frac{F_{\max}}{A} \quad (2)$$

159 where  $F_{\max}$  is the maximum recorded force, and  $A$  is the effective loaded area of the specimen.

160 The modulus of elasticity was computed based on the records of the vertical displacement  
161 transducers. The results of the compressive strength and modulus of elasticity are presented in  
162 Table 2.

163 Regarding the mechanical properties of masonry walls, it is obvious that the mechanical  
164 characteristics of the masonry walls directly depend on constituent materials. Besides that, the  
165 quality of the workmanship is effective. From the tests conducted by Pires [19] it can be  
166 concluded that the quality of the mortar and workmanship have a strong influence on the  
167 masonry shear strength, however, not a significant influence on the compressive strength.

168 The concrete compressive strength of the frame was evaluated at 28 days by direct compression  
169 tests on cubes of  $150 \times 150 \times 150 \text{ mm}^3$ . The average of cubes concrete compressive of 12  
170 specimens was 44.23 MPa. The values of tensile properties of the steel bars were obtained from  
171 uniaxial tensile tests. The average value of the yield stress of the steel bars of 10, 16, and 20 mm  
172 diameter were 540, 533, and 618 MPa, respectively, while the average value of the tensile  
173 strength for these corresponding bars were 570, 640, and 720 MPa, respectively.

#### 174 *Test setup*

175 In reality, if a column is removed from an RC structure the beam-column joints at top start to  
176 move downward. While, in this experimental program, a quasi-static load was applied by using a  
177 closed-loop servo controlled hydraulic actuator at the bottom side of column (Fig. 1) and the  
178 column pushed up due to the limitation of laboratory. The general arrangement of the test setup

179 is shown in Fig. 1. All the three phases were run in a displacement-controlled mode at a rate  
180 equal to 0.01 mm/s. The vertical deflection of the frame was measured with one LVDT at the  
181 location of the applied load. The out of plane movement of the frame was recorded by two  
182 LVDTs. The strain in the longitudinal reinforcement of the columns and beams were measured  
183 by 40 strain gages (Fig. 1a). These strain gages helped to be sure the frame was in elastic regime  
184 and steel longitudinal reinforcement did not reach their yielding in first and second phase of the  
185 test. The right side of RC frame was fixed to rigid floor of laboratory by using two pre-stress  
186 steel bars. The right bottom part of RC frame is also fixed to the rigid wall as shown in Fig. 1a.  
187 Two LVDTs were installed to assure a rigid support in top and bottom parts of the frame as  
188 shown in Fig. 1a.

189 The testes were monitored by using one global (#5) and four local high-resolution cameras (#1 to  
190 #4) to capture the deformed shape of the frame and behavior of the beam-column connection,  
191 respectively. The positions of the cameras are presented in Figs. 1a and 2b. The surface of the  
192 frame and wall were painted white for better detection of the targets on the pictures. To capture  
193 the global behavior of the frame, 30 big targets were painted at a distance 500 mm (Figs. 1b and  
194 2b). To the local analysis of the beam-column connection, a regular grid of circular target was  
195 painted in a rectangular area ( $1450 \times 1100 \text{ mm}^2$ ) at 50 mm in both direction [20].

196

### 197 **Results and discussion:**

198 The load deflection diagram of the tested frame in three different phases is presented in Fig. 5a.  
199 The corresponding load at 30 mm deflection of each individual phase is also presented in Table  
200 3. According to the results presented in Fig. 5a, the behavior of the tested frame with and without  
201 masonry infill wall is almost linear up to a certain limit load. While, the linear part of the load-

202 deflection curve of the F-Tr frame is also more lengthened compared with the bare frame, due to  
203 higher lateral strength provided by masonry units.

204 The tested carried out for the F-Tr frame was stopped at a deflection of 32 mm due to the failure  
205 of the masonry wall (crushing of compressive strut). From the obtained results, the  
206  $\Delta F_{\max} / F_{\max-30}^{F-Re} = (F_{\max-30} - F_{\max-30}^{F-Re}) / F_{\max-30}^{F-Re}$  ratio was evaluated, and the values are indicated in  
207 Table 4, where  $F_{\max-30}^{F-Re}$  and  $F_{\max-30}$  are the maximum load capacity of the reference frame (F-Re)  
208 and of the other frames at deflection of 30 mm, respectively. It was calculated the  $\Delta F / F^{F-Re}$   
209 ratio where  $\Delta F$  is the increase in load provided by infilled masonry walls ( $\Delta F = F - F^{F-Re}$ ),  
210 being  $F^{F-Re}$  the load capacity of the reference frame, and  $F$  the corresponding (for the same  
211 deflection) load capacity of the other infilled frame. The  $\Delta F / F^{F-Re}$  (%) vs. corresponding  
212 deflection curves at loaded section are depicted in Fig. 5b, and their maximum values  
213  $(\Delta F / F^{F-Re})_{\max}$  are presented in Table 3. According to the results presented in Fig. 5b and Table  
214 3, the initial stiffness can increase approximately 500% for the infilled frame compared to the  
215 bare frame (F-Re). According to Fig. 5b, it can be concluded that the F-Re and F-B tests had a  
216 similar behavior in elastic regime. The negative results obtained for F-B test is because of the  
217 micro cracks formed at the top and bottom beams when the frame was tested in the first phase.

218 The increasing frame deflection at the point of the missing column support is restrained due to  
219 the structural resistance of the masonry infill wall and its composite action with the surrounding  
220 RC frame that cause developing interaction forces between the infill wall and the surrounding  
221 frame [20]. At a vertical displacement of around 7.5 mm in F-Tr frame, a horizontal crack was  
222 formed between the masonry brick and RC frame (red ellipse in Fig. 6a). By increasing the load,  
223 the crack propagated and gradually widened in the later stage. After the formation of the main

224 crack a few cracks formed and propagated into the masonry bricks (Fig. 6b) due to compressive  
225 arch. Fig. 6b shows the crack pattern of the infilled frame at a vertical displacement of 30 mm.  
226 The failure of the bare frame was governed by formation of plastic hinges at the beams ends as  
227 expected due to design approach of the frame according to EC8 (strong columns and weak  
228 beams) [14].  
229 Toughness indicator, as a measure of the energy absorption capacity, is obtained for the tested  
230 frame up to 10 mm and 30 mm by determining the area behind the force vs. deflection curve  
231 (Table 4). According to results presented in Table 4, the tested frame in the first phase (F-B) had  
232 a behavior like that the tested frame in the last phase (F-Re) in elastic regime since both had a  
233 same amount of toughness up to 10 mm and 30 mm. The toughness of F-Tr frame is  
234 approximately 4 times and 2.7 times higher than the bare frame (F-Re) up to a deflection of  
235 about 10 mm and 30 mm, respectively. That indicates the contribution of masonry infill wall to  
236 increase the strength and stiffness of RC frame.

237

### 238 **Photogrammetry:**

239 As mentioned in introduction, the behavior of the frame under vertical load was monitored using  
240 photogrammetry technique [21]. For this purpose, five high resolution cameras were used in 5  
241 different stations. Four cameras (#1 to #4) used to monitor the local behavior of the joints and  
242 interaction between wall and surrounding RC frame and one camera (#5) just monitored the  
243 global behavior of the frame. To recognize the possibility of error in photogrammetry technique,  
244 the results obtained by LVDT and photogrammetry for each phase in different stage are  
245 presented in Table 5. According to the results, the average ratio of measured vertical

246 displacement by LVDT to photogrammetry technique is 0.98 with a COV of 7.86%, that shows  
247 the accuracy of the photogrammetry technique.

248 Figure 7 shows the deformation of the frame in each load stage. The deformation was obtained  
249 by measuring the displacement in each painted global target in beams and columns. According to  
250 the results, it can be concluded that the columns did not show significant rotation in any of each  
251 test that can be explained by the fact that there was a complete fixed support in the other side.

252 As mentioned before, the loss of a column causes significant increase of the frame deflection that  
253 is restrained by the shear resistance of the masonry infill wall, thus developing interaction forces  
254 between the infill wall and the surrounding frame [20]. According to analysis of F-Tr test at  
255 station #3 and stage #5 (Fig. 8a), on the initial stage of loading, the load had equally distributed  
256 through the column and beam as well as the masonry wall, while this distribution was not more  
257 uniform after formation of the horizontal crack and separation of the infill wall from the beam  
258 (Figs. 8b)

259

### 260 **Macro modeling:**

261 Macro finite element model analysis was carried out by OpenSees [15] to investigate the  
262 behavior of the tested frame in different phases. Parametric studies were carried out to further  
263 study the effect of the longitudinal reinforcement ratio on the load carrying capacity. The column  
264 was pushed up by displacement to simulate loading strategy in the experimental program.

#### 265 *Constitutive model and its predictive performance*

266 Beams and columns were modeled using force-based elements, with five integration points along  
267 each element length and Corotational Coordinate Transformation for geometric nonlinearity.  
268 Three layers of fibers in the cover region and twenty layers of fibers in the core region were

269 assigned to model the beam and column cross sections. The values of the parameters that define  
270 constitutive models used in numerical simulation were calibrated by simulating the tested frame,  
271 considering the properties obtained in the experimental programs for the characterization of the  
272 relevant properties of the used materials, and the suggestion of the EC2 [13].

273 The material “Concrete02” available in OpenSees was used for the concrete frame. The  
274 constitutive model of this block is presented in Fig. 9a, where  $f_{pc}$  is concrete compressive  
275 strength at 28 days,  $\varepsilon_{psc0}$  is concrete strain at maximum strength,  $f_{pcu}$  is the crushing strength,  
276  $\varepsilon_{psu}$  is the strain at crushing strength,  $\lambda$  is the ratio between unloading slope at  $\varepsilon_{psu}$  and initial  
277 slope,  $f_t$  is the tensile strength, and  $E_{ts}$  is the tension softening stiffness (absolute value). More  
278 information on this constitutive model can be found in Opensees [15]. The values of this diagram  
279 are presented in Table 6. As mentioned before, the concrete compressive strength of frame is  
280  $f_{pc} = 44.23$  MPa. Then other parameters can be found based on EC2 [13],  $\varepsilon_{psc0}$  and  $\varepsilon_{psu}$  are  
281 equal to 0.0027 and 0.0035, respectively.  $f_{pcu}$  is 30 MPa, and  $f_t = 2.7$  MPa.  $\lambda$  and  $E_{ts}$  were  
282 calibrated by simulating the tested frame.

283 The material “Steel01” available in Opensees is used to define the reinforcement of columns and  
284 beams. This is a elasto-plastic with hardening model, where the stiffness of the post-yield branch  
285 is controlled by the strain-hardening ratio  $b$ , given by the ratio between the post-yield tangent  
286 and initial tangent (Fig. 9b). More information on this constitutive model can be found in  
287 Opensees [15].

288 The contribution of the masonry walls was implemented using the eccentric truss element as  
289 suggested by Al-Chaar and Lamb [16], the strut width  $a$  for a solid infill can be estimated as  
290 follows:

$$a = 0.175 \times D \times (\lambda L)^{-0.4} \quad (3)$$

291

292 where  $\lambda$  is:

$$\lambda L = L \times \sqrt[4]{\frac{E_m \times t \times \sin(2\theta_b)}{4 \times E_c \times I_{beam} \times l}} \quad (4)$$

293 The strut width ( $a$ ) is dependent of the relative bending stiffness between the beams and the

294 masonry panel ( $\lambda L$ ). The distance  $Lb$  represents the length of formation of plastic hinges and is

295 determined geometrically (Figure 10):

$$Lb = \frac{a}{\sin(\theta_b)} \quad (6)$$

296 where:

$$\tan(\theta_b) = \frac{h}{l - 2Lb} \quad (8)$$

297 In Equation 4,  $L$  is the distance between the columns midlines,  $l$  is the masonry panel width,  $t$  is

298 the panel thickness,  $E_m$  refers to the modulus of elasticity of masonry,  $E_c$  represents the

299 modulus of elasticity of concrete,  $I_{beam}$  is the moment of inertia of the beams. In Equation 3,  $D$  is

300 the diagonal length of the panel. The strut material is assumed Kent-Scott-Park model [15].

301 According to the test results of masonry bricks, maximum compressive strength for the model is

302 assumed 1.2 MPa with corresponding strain of 0.0022, the crushing strength is 0.1 with

303 corresponding strain of 0.005.

304 A model of infill wall (F-Tr) is presented in Fig. 11. In this model, it was assumed that the

305 masonry infill had a compressive linear elastic behavior and do not resist tension stresses. By

306 using the properties obtained from the mechanical properties of masonry and deriving from

307 inverse analysis the data for the masonry infill model was found. The experimental and the

308 numerical relationships between the applied load and the deflection at the loaded section for the

309 tested frame in different phases are presented in Fig. 12. This figure also shows a comparison  
310 between experimental and numerical simulation in terms of strain-load relationship. This figure  
311 shows that the numerical model can capture with high accuracy the deformational response and  
312 strain in longitudinal bars of the tested frame in different phases.

### 313 *Parametric Study:*

314 Due to the good performance of the adopted model in simulating the behavior of the structure,  
315 confirmed in the previous section, the model was adopted to study the influence of percentage of  
316 longitudinal reinforcement ratio in beams and columns on the load carrying capacity of the  
317 frame. For this purpose, the area of the longitudinal reinforcement implemented in OpenSees  
318 [15] was changed to simulate the effect of the longitudinal reinforcement. The geometry of  
319 beams and columns, the material properties of concrete, the support and load conditions, and the  
320 length of the elements were those adopted in the previous section.

### 321 *Influence of longitudinal reinforcement ratio of the columns*

322 In this case, the influence of columns longitudinal reinforcement ratio on the load-deflection is  
323 investigated. For this purpose, two different percentage of column reinforcement ratio are  
324 assumed: 1% and 6%, the first one is lower and the last one is higher than the one corresponding  
325 to the percentage of the columns reinforcement of the tested frame.

326 The obtained results, depicted in Fig. 13, show that the high percentage of reinforcement does  
327 not have effect on the load carrying capacity of RC frame. Because, as mentioned before, the  
328 failure of the bare frame was governed by formation of plastic hinges at the beams ends, then  
329 increasing the longitudinal reinforcement of columns does not have influence on the load  
330 carrying capacity. The load carrying capacity of the with 2.7% and 6% longitudinal  
331 reinforcement are around 23% higher than the frame with 1% of longitudinal reinforcement.

332 *Influence of longitudinal reinforcement ratio of the beams*

333 Figure 14 shows the obtained results for different beams longitudinal reinforcement ratio. Two  
334 different percentage of beams longitudinal reinforcement are assumed: 0.5% and 1.5%, the first  
335 one is lower and the last one is higher than the one corresponding to the percentage of the beams  
336 reinforcement of the tested frame.

337 As expected, by increasing the longitudinal reinforcement ratio of the beams, the load carrying  
338 capacity and ultimate deflection is increased. The load carrying capacity of frame with 1.5%  
339 longitudinal reinforcement is around 19% and 72% higher than the one in frame with 0.96% and  
340 0.5% longitudinal reinforcement, respectively.

341 *Influence of longitudinal reinforcement ration of both beams and columns*

342 Figure 15 shows the obtained results for different beams and columns longitudinal reinforcement  
343 ratio. In this study, two different percentage of longitudinal reinforcement are assumed: 50%  
344 more and 50% less than longitudinal reinforcement ratio of the tested frame.

345 In the first case, RC frame with 50% more longitudinal reinforcement, and similar to the  
346 experimental test observations, masonry has significant impact on frame stiffness and negligible  
347 influence on the strength. In the second case, RC frame with 50% less longitudinal  
348 reinforcement, it is clear the significant impact of the masonry infill wall on both the stiffness  
349 and the strength of the RC frame. Therefore, it can be stated that, for current RC frames, it is  
350 expected that masonry infill wall has a significant contribution to the structural robustness,  
351 namely by providing an alternative load path in the event such as a column failure.

352

353

354 **Conclusions:**

355 Progressive collapse of multistory buildings can occur after local damage to a member typically  
356 initiated by extreme dynamic events such as earthquake, natural disasters, and terrorist attack.

357 This paper studied the effectiveness of traditionally bricks masonry units on the behavior of  
358 reinforced concrete (RC) frame subjected to vertical load. The frame was designed according to  
359 Eurocode 2 (EC2) and Eurocode 8 (EC8). The frame was designed to have strong columns and  
360 weak beams. The results enhance the understanding regarding the behavior of frame with and  
361 without infill wall and its contribution on the structural robustness. According to the results  
362 obtained by experimental results, it can be concluded that:

- 363 • The quality of the mortar and workmanship have a strong influence on the masonry shear  
364 strength, however, not a significant influence on the compressive strength.
- 365 • The infill wall plays a major role in maintaining the structural system's integrity and  
366 reducing the likelihood of a progressive collapse and therefore its contribution should be  
367 incorporated in the structural model.
- 368 • Traditionally infill wall can significantly increase stiffness and load carrying capacity of a  
369 RC frame at a certain deflection around 220% compare to a frame without any infill wall.
- 370 • The masonry walls can increase the energy absorption and that the toughness of the  
371 infilled frame 270% higher than the ones without infilled wall.
- 372 • Compared with the bare frame, the infilled frame has a larger initial stiffness but lower  
373 ductility.

374 Artificial vision system was used as a structural monitoring system. This technique provides  
375 important data in terms of interaction of infill wall and surrounding RC frame. The loss of a  
376 column causes developing interaction forces between the infill wall and the surrounding frame  
377 which this interaction and its propagation have been clearly shown by artificial vision.

378 A numerical simulation was carried out using the OpenSees software. The values of the  
379 constitutive models were calibrated considering the properties obtained from the tests of the

380 material properties, inverse analysis, and the suggestion of EC2. After having been demonstrated  
381 that the model is capable of simulating, with high accuracy a parametric study was carried out to  
382 investigate the influence of the percentage of longitudinal reinforcement ratio in beams and  
383 columns on the load carrying capacity of the infilled frame. Results presented that:

- 384 • When the failure is governed by formation of plastic hinges at the beams the high  
385 percentage of reinforcement of column does not have effect on the load carrying capacity  
386 of the frame.
- 387 • while high percent of longitudinal reinforcement of beams can significantly increase of  
388 the load carrying capacity of the farm.
- 389 • The frame reinforcement details have a pronounced effect on the frame performance.

390

## 391 **ACKNOWLEDGMENTS**

392 The authors gratefully acknowledge the funding by Ministério da Ciência, Tecnologia e Ensino  
393 Superior, FCT, Portugal, under grants of PTDC/ECM-COM/2911/2012.

## 394 **REFERENCES:**

395 [1]. Ellingwood, B. R.; Leyendecker, E. V. (1978). "Approaches for design against progressive  
396 collapse". *Journal of the Structural Division*. 104 (3): 413–423. A progressive collapse is a chain  
397 reaction type of failure which follows damage to a relatively small portion of a structure.

398 [2]. Cachado, A., Grilo, I., Júlio, E., and Neves, L., "Use of Non-Structural Masonry Walls as  
399 Robustness Reserve", in 35th Annual Symposium of IABSE, 2011, IABSE / IASS: London.

400 [3]. Baghi, H., Oliveira, A., Cavaco, E., Neves, L., Júlio, E. (2016) "Experimental testing of RC  
401 frames with masonry infills subjected to a column failure" RF2016 5th International Conference  
402 Integrity-Reliability-Failure. Faculty of Engineering/U. Porto2016

403 [4]. Farazman, S., Izzuddin, B. A., Cormie, D., "Influence of Unreinforced Masonry Infill Panels  
404 on the Robustness of Multistory Buildings". *Journal of Performance of Constructed Facilities*,  
405 2013. 27(6): p. 673-682.

- 406 [5]. Sorensen J. D., R.E., FABER M.H., Robustness – Theoretical Framework, in Joint  
407 Workshop of COST Actions TU0601 and E55, 2009: Ljubljana, Slovenia. p. 27-34.
- 408 [6]. Mondal, G., Tesfamariam, S., "Effects of vertical irregularity and thickness of unreinforced  
409 masonry infill on the robustness of RC framed buildings", *Earthquake Engineering & Structural  
410 Dynamics*, 2013. 43(2): p. 205-223.
- 411 [7]. Shan, S., Li, S., Xu. S., Xie, L., "Experimental study on the progressive collapse  
412 performance of RC frames with infill walls" *Engineering Structures*, 111 (2016) 80–92
- 413 [8]. Tsai MH, Huang TC. Effect of interior brick-infill partitions on the progressive collapse  
414 potential of a RC building: linear static analysis results. *Int J Eng Appl Sci* 2010;6(1):1–7.
- 415 [9]. Tsai MH, Huang TC. Numerical investigation on the progressive collapse resistance of an  
416 RC building with brick infills under column loss. *Int J Eng Appl Sci* 2011;7(1):27–34.
- 417 [10]. Tiago, P., Júlio, E., "Case-Study: Damage of an RC Building after a Land-Slide -  
418 Inspection, Analysis and Retrofitting", *Engineering Structures*, 32 (7): 1814-1820, 2010.
- 419 [11]. Pujol, S., Benavent-Climent, A. , Rodriguez, M., Smith-Pardo, P., "Masonry infill walls: an  
420 effective alternative for seismic Strengthening of low-rise reinforced concrete building  
421 Structures", in The 14th World Conference on Earthquake Engineering, 2008: Beijing, China.
- 422 [12]. Sasani, M., "Response of a reinforced concrete infilled-frame structure to removal of two  
423 adjacent columns", *Engineering Structures*, 2008. 30: p. 2478–2491.
- 424 [13]. CEN, Eurocode 2. "Design of concrete structures—part 1–1: general rules and rules for  
425 buildings", 2004, EN 1992-1-1:2004:E.
- 426 [14]. CEN, Eurocode 8. "Design of structures for earthquake resistance - Part 1: General rules,  
427 seismic actions and rules for buildings", 2004, EN 1998-1:2004.
- 428 [15]. Opensees, Concrete02 Material - Linear Tension Softening, 2015: University of Berkeley.
- 429 [16]. Al-Chaar, G.K. and Lamb, G.E., Design of Fiber-Reinforced Polymer Materials for Seismic  
430 Rehabilitation of Infilled Concrete Structures, 2002, DTIC Document.
- 431 [17]. BS EN 1052-3 "Methods of test for masonry. Determination of initial shear strength", 2002,  
432 EN 1052-3:2002.
- 433 [18]. BS EN 1052-1 "Methods of test for masonry. Determination of compressive strength",  
434 1999, EN 1052-1:1998.
- 435 [19]. Pires, F., Influência das paredes de alvenaria no comportamento de estruturas reticuladas de  
436 betão armado sujeitas a acções horizontais. Tese Doutoramento. Laboratório Nacional de  
437 Engenharia Civil.1990. Lisboa LNEC, in Portuguese.

438 [20]. Brodsky, A., Yankelevsky, D.Z., " Resistance of reinforced concrete frames with masonry  
439 infill walls to in-plane gravity loading due to loss of a supporting column" *Engineering*  
440 *Structures 140 (2017) 134–150*.

441 [21]. Filipa Borges Marques, 2016, "Monitoring concrete frames with brick walls using  
442 photogrammetry", Master thesis, Universidade NOVA de Lisboa, in Portuguese.

443

444

445

446

447

448