

A target-driven decision-making multi-layered approach for optimal building retrofits via agglomerative hierarchical clustering: A case study in China

Hong, Y.^{1,2,3}, Ezech C. I.³, Zhao H.⁴, Deng, W.^{2,*}, Hong, S-H.², Tang, Y.⁵

1 = Laboratory for Manufacturing and Productivity
Massachusetts Institute of Technology
77 Massachusetts Avenue, Cambridge, MA, USA

2 = Department of Architecture and Built Environment
University of Nottingham Ningbo
University Park, Ningbo, China

3 = Shanghai Daren Construction Engineering Co. Ltd
Lianhang Road, Minhang District, Shanghai, China

4 = Shenzhen Institutes of Advanced Technology
Chinese Academy of Sciences
University Town of Shenzhen

5 = Department of Architecture and Built Environment
University of Nottingham UK
University Park, Nottingham, UK

* corresponding email = Wu.Deng@nottingham.edu.cn

Abstract

The optimisation of energy, environmental and economic (3E) outcomes is the principal approach to identifying retrofit solutions for a sustainable built environment. By applying this approach and defining a set performance target, this study proposes a makeshift decision framework that integrates a data mining procedure (agglomerative hierarchical clustering (AHC)) into the decision-making process to provide a simplified 3E assessment of building retrofits on a macro-scale. The framework comprises of three model layers: (1) a building stock aggregation model, (2) an individualistic 3E model that provides the sensitivity analysis for (3) a life cycle cost-environmental assessment model. The framework is demonstrated and validated with a case study aimed at achieving the set energy targets for low-rise office buildings (LOB) in Shanghai. The model defines 4 prototypical buildings for the existing LOB blocks, which are used for the individual evaluation of 12 commonly applied retrofit measures. Subsequently, a simplified LCC-environmental assessment was performed to evaluate the 3E prospects of 2048 possible retrofit combinations. The results uniquely identify retrofit solutions to attain set performance targets and optimal building performance. Furthermore, the decision criteria for different investment scenarios are discussed. Overall, this study

provides building investors an innovative framework for a facile and holistic assessment of a broader range of retrofit alternatives based on set performance targets.

Keyword: retrofit measures, cost analysis, life-cycle cost, *agglomerative hierarchical clustering*, low-rise office

1. Introduction

1.1. Background

Utilizing building retrofits has emerged as the primary concept for achieving a sustainably conscious society [1]. However, identifying the most suitable retrofits is hindered by many constraints associated with their implementation such as climatic condition, building typology, regulations and policies [2]. Typically, the application of numerous optimisation approaches (single-objective [3, 4] or multi-objective [5-7]) addresses this difficulty. Recent studies have demonstrated that a multi-objective optimisation approach is more suited to establish an optimal retrofit solution [8]. In this approach, the universal concept of optimising the energy, environmental and economic (3E) variables is emphasised to promote the interpretability, applicability and comparability between outcomes [1, 9, 10]. Social variables of building retrofits, such as the best possible compromise to enhance thermal comfort and indoor air quality, are also commonly considered [8, 11, 12].

Common multi-objective optimization algorithms adopt the simultaneous optimization of decision variables using a set of objective functions. The jointly considered decision variables are electricity consumption, CO₂ emission and cost indicators (investment, energy, life-cycle or payback period (PBP)). The optimization of these variables are defined by the objective functions, which commonly involve minimising the life-cycle costs (LCC) [6, 13]; maximising energy conservation (energy reduction impact), renewable sources adaptability and conservation compatibility [6, 7, 14]; and minimising CO₂ and in some cases, other greenhouse gas (GHG) emissions [3, 5]. Despite the numerous algorithms that provide advice on building retrofits, decisions regarding the optimal combinatorial retrofit solution with minimum cost for a specific building typology are typically complex. Limited by the available budget to achieve the provincial set energy target, the optimal retrofit solution may combine low-cost retrofit measures (that have an insignificant impact on energy savings) to a high-cost measure (with potential to establish a net zero energy (NZE) building). Therefore, the optimal retrofit solution should not only be defined by the stakeholders' initial budget, but also to maximise the long-term benefits of energy performance. On this basis, the LCC approach, which provides a more realistic evaluation to stakeholders is relevant.

Generally, the objective function for an optimal retrofit should be an economical solution with minimal energy consumption and environmental impact. Nevertheless, most studies have only established this objective for designated typical buildings (micro-scale intervention) rather than for the entire building stock (meso- or macro-scale) [7, 14]. The implementation of energy efficiency policies concentrates on macro-scale interventions. Hence, recent studies focus on establishing an evaluating model framework with an appropriate approach for retrofitting existing buildings on a macro-scale [15]. In 2015, Lotteau and coworkers reported that the various adaptation of environmental assessment is the common approach for neighbourhood scale evaluation of the built environment in most reviewed studies [16]. Most recently, Mastrucci and coworkers pinpointed energy and environmental assessment models as the common framework for macro-scale evaluation [17]. However, to improve the interpretability of the results and comparability between outcomes, an economic indicator in addition to the potential energy and environmental impact indicators is recommended [15, 16]. Broadly, it is uncommon to find studies on optimum energy retrofits on a macro scale with three or more objective functions owing to the complexities and uncertainties associated with the application of the approach on a broad scale.

Therefore, to bridge the abovementioned gaps, a macro-scale evaluating model with a coordinated LCC-environmental valuation approach for a facile and holistic assessment of the 3E variables is necessary. Most importantly, the model will be meaningful to support decisions in sustainable urban planning and policymaking, particularly for developing societies. Accordingly, the model should proffer decisions based on investors' priority and set performance targets within that city/area.

1.2. Novelty and contribution of this paper

Given the present state of the art and considering the strengths and weaknesses of the outlined literature background, the novelty of this paper lies in the adoption of a comprehensive approach to providing a holistic (3E) evaluation of building retrofits on a macro-scale. While literature review emphasizes the complexities and lack of robust application of several decision-making models on a broader scale, this study highlights a model framework with a facile assessment methodology. The proposed approach incorporates a data mining analysis (agglomerative hierarchical clustering (AHC)) into a multi-objective decision-making process to aid building stakeholders in selecting appropriate retrofit solutions under possible scenarios on a macro-scale. There are five main advantages to this approach:

- *Ab-initio* prototyping of existing building stocks via AHC
- All 3E-assessed retrofit strategies are compared, not only to each other but also to the performance targets set by standards and regulations.

- 1 • Assessment of a broader range of retrofit measures under the energy demand-
2 side, energy supply-side and energy-conserving groups.
- 3 • Adopting AHC pair-wise comparison to establish the most appropriate retrofit
4 solution.
- 5 • Establishing rational decision criteria based on the performance targets that can
6 be adapted to stakeholders' priorities.

7 The paper is structured as follows. Section 2 describes the **coordinated** multi-objective
8 decision-making model. In Section 3, the proposed model is demonstrated using a case
9 study analysis. The design considerations, performance targets, outcomes and
10 validation are described in this section to establish a novel user-oriented retrofit solution.
11 Finally, some concluding remarks are made in Section 4.

12

13 **2. Model framework and methodology**

14 **2.1. Model framework with a novel approach of assessing building retrofits on a** 15 **macro-scale**

16 The model framework is based on three **coordinated model layers**: (1) a building stock
17 aggregation model, (2) an individualistic 3E model that provides the sensitivity analysis
18 for (3) a life cycle cost-environmental assessment model (which initiates the decision-
19 making criteria) (see Fig. 1). In this study, the model framework assumes that an urban
20 building model (with sufficient aggregated data of building stocks at building level) is
21 not available in developing societies.

22 The building stock aggregation model is used to describe the existing buildings under
23 investigation. It involves the characteristic-based evaluation of building energy
24 performance to develop the relevant building prototypes, which will serve as the
25 foundation for subsequent evaluations. Further explanation of this model is described
26 in the literature [17]. However, the novelty of this study lies in the use of AHC
27 technique to refine the generated non-dominated performance indexes during the
28 building classification process to make it more intuitive and presentable.

29 The second model involves the individualistic 3E simulation of selected retrofit
30 measures on the prototypical buildings. Simulation input variables are collected from
31 literature, surrogate sources, questionnaire survey and on-site measurements. This
32 model provides the sensitivity analysis based on selected decision variables required
33 for subsequent analysis. In this study, the selected decision variables are electricity
34 consumption, CO₂ emission and cost indicators (investment costs (IC) and PBP).

35 The results from the individualistic 3E model are then used as the input data for the
36 LCC-environmental assessment model, which is employed to evaluate the benefits of

1 the combinatorial retrofit measures via a set of simplified numerical simulations. The
2 LCC approach serves as a makeshift economic & energy evaluating model as it depicts
3 the trend between retrofit costs and energy-saving benefits. Here, the universal concept
4 of minimizing the total LCC defines a set of optimal combinations of retrofit strategies
5 [8, 12]. By integrating the LCC approach with an environmental assessment model, a
6 unique optimal strategy is obtained. It is highly recommended that LCA is employed
7 as the assessing model to provide a comprehensive tracking of all air-, water- and land-
8 borne emissions. However, considering the high environmental burden of CO₂ emission
9 as well as the fact that CO₂ emissions is the most commonly investigated environmental
10 indicator for buildings [8, 18], this study restricts the environmental assessment to the
11 CO₂-savings potential of the retrofit measures.

12 Also, this model framework simultaneously provides a range of suitable retrofit
13 solutions for attaining the performance targets as stipulated by the set standards and
14 regulations. Using an AHC data mining technique for pairwise comparison, the non-
15 dominated solutions can be further refined to identify the most probable solution for a
16 macro-scale intervention [19]. Furthermore, by comparing the 3E benefits of the
17 optimal retrofit solution to that for attaining the regulated performance targets, a set of
18 decision indicators/criteria to guide investors in selecting the most reasonable solution
19 is described. Overall, the proposed framework presents a decision-making model
20 anchored on a clustering technique for a facile and holistic 3E assessment of a broader
21 range of retrofit measures.




Fig. 1. Proposed macro-scale approach for retrofitting existing building blocks

2.2. Research methodology

2.2.1. Building stock aggregation and prototyping

The detailed description of this methodology is presented in our previous study [20]. Due to the lack of sufficient aggregated data, this methodology uses empirical databases generated from a large-scale survey of building samples and top-down macro-economic and statistic tools. Pearson and Biserial correlation analyses are adopted to define the

performance index system (PIS) of the building energy efficiency. Given the large data size, further index refinement is conducted using cluster analysis. For simplicity and control of variables, the squared Euclidean distance and Z-score standardization methods [21] are used as the similarity metric and for data normalization, respectively. By employing the clustering technique, a facile approach for identifying the key performance indexes (KPIs) is established, which are then used for building classification and prototyping. Each prototype represents a specific class of buildings that can be used to extrapolate the energy requirements of the entire stock.

2.2.2. Assessment of the individualistic retrofit measures

The assessment of the 3E impact of each retrofit measure on the prototypical buildings is conducted using a building performance modelling (Integrated Environmental Solutions Virtual Environment (IES-VE)) software. IES-VE has demonstrated a high level of accuracy and interoperability in estimating and predicting building performance [22]. Precise assessment by the software is supported by the integrated BIM platform that considers the interaction between the retrofit measures. For example, by replacing lighting with LED lighting, the impact on indoor heat gains is considered in the simulation when the simulation conditions are set in the Building Template Manager. However, a comprehensive analysis on such interactive impacts should be further investigated if they are not included in the simulation settings. For a more accurate simulation, measured weather data of the region was used. Thereafter, the simulation results for each prototype are compared with their original model to estimate their respective 3E impact of the measures.

2.2.3. Assessment of the 3E impact for all possible combinatorial retrofit strategies

To precisely estimate the impact of all possible combinatorial retrofit strategies, it is crucial to consider that the measures in a particular retrofit strategy interact with each other. Hence, an appropriately integrated simulation of all the possible combinatorial retrofit measures is required. However, a simulation of this magnitude is impractical and requires a high computational cost. Therefore, a more numerical approach for the LCC evaluation using the individually pre-simulated 3E results is recommended, but with a critical simplification to reduce calculation complexities.

The emphasis is on the LCC framework, which consists of nine steps. Readers are kindly referred to the literature for the LCC principles [23].

- Step 1: To calculate the IC for each combinatorial retrofit strategy as the sum of the IC of all included retrofit measures.

- Step 2: To calculate the annual energy cost (EC) for each strategy (which indicates the energy impact) using:

$$EC = E_T \times EP \quad (1)$$

where E_T is the annual energy consumption (as computed in Section S1.1) and EP is the price per unit electricity.

- Step 3: To calculate the total LCC for each strategy, as illustrated in Section S1.2.
- Step 4: To classify the retrofit development level (DL) using the IC values. Here, the IC values are sorted in ascending order and serve as the basis for rating the DL from 0-100%. The strategy with no retrofit activity has a DL of 0%, and the strategy with all retrofit activities has a DL of 100%.
- Step 5: To reduce the computational complexity due to the high number of data points by using the average of an 8-point bin of the DL, IC, EC, and total LCC as the new data points for the graph plotting.
- Step 6: To generate the IC, EC, and total LCC profiles based on the DL with a reasonable R^2 correlation coefficient.
- Step 7: To determine the optimal retrofit solution at the minimum LCC (LCC_{min}) with an environmental assessment model.
- Step 8: Using the generated profiles, a building performance threshold required to achieve the set performance targets is established. By calculating the required reduction in a selected variable to attain the set targets, a threshold IC value to achieve this variable change is estimated. All retrofit solutions with IC value beyond this threshold is considered suitable for attaining the set targets.
- Step 9: Finally, adopting the AHC data mining technique to determine the centroid strategy that represents all the possible retrofit solutions beyond the threshold value.

Finally, by comparing the 3E benefits from Step 7 and Step 9, a set of decision indicators/criteria to guide investors in selecting the most reasonable solution is described. These indicators/criteria are further discussed in Section 2.2.5.

2.2.4. Clustering methodology

- Data preprocessing

First, we normalize the aggregated/simulated data using the z-score for effective comparison given the varying magnitude of data values. The z-score standardization method is employed for effective control of data variation and to prevent result skewness. This converts each data (x_i) of a particular i^{th} data group to have zero mean (μ_i) and a standard deviation (σ_i) of 1. The z-score (Z_{x_i}) is computed as:

$$Z_{x_i} = \frac{x_i - \mu_i}{\sigma_i} \quad (2)$$

- Cluster analysis

To refine the generated non-dominant data towards the set objectives, an expanded two-step clustering method that combines an AHC with the k -means algorithm is employed. The first step involves the AHC algorithm. This is a bottom-up procedure where each data is initialized as a cluster and as the algorithm proceeds, clusters are further merged pairwise. Here, the goal is to minimize the squared Euclidean distance, d between two datasets (x and y). For simplicity, the *ward* criterion is adopted for the minimisation.

$$d = \sum_{i=1}^I (Z_{x_i} - Z_{y_i})^2 \quad (3)$$

Besides, the algorithm defines the k values of potential clusters and identifies possible outliers without any preconception by the user [24]. Also, it generates a dendrogram (tree-like diagram) presenting a visual interlink of the clusters.

Following the identification of the number of clusters ($\mathcal{C} = \{C_1, C_2, \dots, C_k | k \leq N\}$) and the associated k values for a set of N data ($x_1, x_2, \dots, x_n$), the k -means algorithm for partitioning around a centroid is implemented as the second step. Here, the objective is to minimize the within-cluster variance so that:

$$\underset{\mathcal{C}}{\operatorname{argmin}} \sum_{i=1}^k \sum_{x \in C_i} \|x - \mu_i\|^2 = \underset{\mathcal{C}}{\operatorname{argmin}} \sum_{i=1}^k |C_i| \operatorname{Var} C_i \quad (4)$$

where μ_i is the mean/centroid of data points in C_i .

In this algorithm, random centroids ($\mu_1^{(1)}, \mu_2^{(1)}, \dots, \mu_k^{(1)}$) are initiated and each data point is assigned to the cluster with the nearest centroid via the least squared Euclidean distance:

$$C_i^{(t)} = \left\{ x_a : \|x_a - \mu_i^{(t)}\|^2 \leq \|x_a - \mu_j^{(t)}\|^2 \right\} \quad (5)$$

where x_a is the assigned data point to a cluster $C^{(t)}$.

Then, a new centroid is computed as the average of all data point within the cluster:

$$\mu_i^{(t+1)} = \frac{1}{|C_i^{(t)}|} \sum_{x_j \in C_i^{(t)}} x_j \quad (6)$$

This procedure is repeated until all data points are assigned to a cluster and the cluster assignment converges. All data points belonging to one centroid form a cluster.

2.2.5. Decision indicators/criteria based on the investor type

Following the identification of suitable combinatorial retrofit solutions required to attain the set performance targets and optimal building performance (at $LCC_{\min}$), it is appropriate to decide which of the solutions should be implemented for each building prototype. Generally, the optimal solution is recommended; however, the outcome of the retrofit strategy for the set target may be more favourable when matched with the optimal. The decision on which to be implemented between the two solutions varies with the stakeholder's priority. Using the IC and DL outcomes, two different scenarios are considered to assess the effect of the investor type on deciding a reasonable retrofit solution.

Scenario 1: When the retrofit cost (IC) is the primary concern of the investors. This scenario is very common in developing societies with such investors including owner-

occupant, absent-owner and leasers [8]. In such scenario, matching the IC of the retrofit solutions for both the set target and minimum LCC (%IC_{ST:LCC}) and comparing it with their matched energy reduction outcome (%ER_{ST:LCC}) offers a facile decision criterion. Here, the more suitable decision will be to invest in the solution for the set target if Equation 7 applies; otherwise, the LCC solution is recommended.

$$\%IC_{ST:LCC} < \%ER_{ST:LCC} \quad (7)$$

where

$$\%IC_{ST:LCC} = \frac{IC_{ST}}{IC_{\min LCC}} \times 100\% \quad (8)$$

$$\%ER_{ST:LCC} = \frac{ER_{ST}}{ER_{\min LCC}} \times 100\% \quad (9)$$

IC_j and ER_j are the investment cost and energy reduction impact at jth target (set performance target or minimum LCC).

Scenario 2: When the investor's priority is the retrofit development level (DL) required to attain a sustainable building. This is another prominent scenario in developing societies with the key investors considered as external stakeholders [8]. In this scenario, the investors are responsible for the environmental implication of each building. In this case, the deciding criterion for retrofit selection is suggested by comparing the matched DL of the retrofit solutions for attaining the set target and the minimum LCC (%DL_{ST:LCC}) with the respectively matched %ER_{ST:LCC}. Here, the likely decision will be to invest in the solution for the set target if Equation 10 applies; otherwise, the LCC solution is more suitable.

$$\%DL_{ST:LCC} < \%ER_{ST:LCC} \quad (10)$$

where

$$\%DL_{ST:LCC} = \frac{DL_{ST}}{DL_{\min LCC}} \times 100\% \quad (11)$$

DL_j is the retrofit development level required to achieve the jth target (set performance target or minimum LCC). Here, the use of percentage changes reduces the error induced by the simplified approach, which ultimately leads to the formulation of innovative and customized deciding indicators/criteria.

3. Case study analysis

3.1. Description of the selected city

In this study, the city of Shanghai, which is one of the most industrial and populous city in the hot-summer-cold-winter (HSCW) climate zone of China [20] is selected. The

city has a large share of old low-rise office buildings (LOB) (50% of the commercial building blocks) [25, 26]. For demonstration, Minhang district is selected as the territorial boundary given that it has the largest non-residential buildings ($6,414 \times 10^4$ m² building area) with a vast age distribution [20]. In total, there are 1486 office building blocks in Minhang with LOB (24 m high or ≤ 6 floors) accounting for 75.4% of the blocks. To promote sustainable urban planning in this city, the old existing LOB requires retrofitting to meet the set energy performance target stipulated in China's regulation.

The prototyping approach employs a large-scale survey of existing LOB in Minhang district, Shanghai. Here, a survey of 10 randomly selected office parks with 136 LOB is conducted. The on-site and surrogate data collected are presented in our previous study [20]. Also, the study describes the proposed prototypical LOB used in this present study. The set performance targets for commercial buildings are detailed in China's outcome-based energy-efficient standard, "Civil Building Energy Consumption Standard", which was developed in 2013 and became effective in 2016 [27]. In this standard, the performance target is presented as annual energy use intensity (EUI) target with a required and recommended value. These values vary with the building typology and its specific characteristics in different climate zones. Table 1 presents the required and recommended EUI targets for different categories of office buildings with 50 years of service life in the HSCW climate zone [27].

Category A defines buildings with operable windows and equipped with split HVAC systems, while category B consists of buildings without operable windows and are mainly served by mechanical ventilation and centralised HVAC systems. In this study, EUI targets under Category A was selected given that most LOB has operable windows with split HVAC systems. Moreover, given that most of the surveyed building blocks are opened to the public, the expected required and recommended EUI targets are 85 kWh/m² and 70 kWh/m², respectively.

Table 1. The outcome-based standard for commercial buildings in the HSCW climate zone [27].

Building Typology	Category	Classification	EUI in HSCW Climate zone (Shanghai), kWh/m ²	
			Required	Recommended
Office	Cat. A	Government	70	50
		Commercial	85	70
	Cat. B	Government	90	65
		Commercial	110	80

3.2. Selected retrofit measures and design standards

The retrofit measures selected for this study follow the region-based prescriptive measures from the design standards for commercial buildings in China [28], Chartered Institution of Building Services Engineers (CIBSE) [29], and other relevant literature [25, 26, 30, 31]. In total, twelve different retrofit measures are selected (see Table 2). The measures are classified into two classes: 1) energy-reducing (which includes demand-side and energy-conserving groups) and 2) energy-producing (primarily consisting of the supply-side group). For a detailed description of the various classification groups, readers are referred to the literature [30, 32]. Section S2 (supporting document) summarises the justification for the selected measures based on our review study on commonly applied building retrofits in Shanghai and their expected design standards [26]. In summary, Table 2 highlights the design standard baseline for each measure. This study assumes that the suggested retrofit measures were not implemented given the current status of the case study buildings.

Table 2. Details of specific retrofit measures

Classes	Group	Activity	Design standards
Original	–	–	Models based on 1980 or 2005 building codes in China [33]
Energy-reducing measures	Energy Conserving Behaviours	1. Occupancy Regimes (Monitoring Strategies)	Adjusting the occupancy period (operating time) from 8:00-18:00 to 9:00-17:00 and monitoring of facilities [29]
		2. Comfort Requirements	Reducing the internal temperature requirement range by 1 °C [29, 34]. During summertime, the temperature set range is changed to 22-29 °C from 22-28 °C. During wintertime, the range is set to 15-24 °C from 16-24 °C [29].
	Equipment/Lighting System	3. Natural Ventilation	The infiltration rate was adjusted from 8.3 l/s to 8 l/s according to CIBSE and adequate monitoring of the windows functions [29].
		4. Replace Lighting with energy-efficient ones	Reducing the lighting power density from 15 W/m ² (before 1980) to 9 W/m ² (according to 2014 building code, GB5018-2014) for buildings before 2005; and from 11 W/m ² (2005 building code GB50189-2005) to 9 W/m ² [28].
		5. Energy-efficient HVAC	Improve the energy-efficiency of heating and cooling equipment to 5.2 chiller COP, 0.9 kW heating SCoP,

Energy-producing measures	Building Envelope		3.5 kW cooling nominal EER and 3.0 kW cooling seasonal EER [28].
		6. Insulate ceilings	add 20 mm XPS insulation material on ceilings [35]
		7. Insulate walls	add 160 mm XPS insulation material on walls [35]
		8. Insulate cool roofs	add 150 mm XPS insulation material on cool roofs [35]
		9. Replace Windows with energy-efficient ones	Replacing windows with energy-efficient ones [36, 37] using 6low-E+12air+6low-E+12air+6low-E triple-glazed windows [35]
		10. Air-tightness	Changing the air-tightness infiltration to $N_a = 0.6$ ach according to CIBSE [29].
	Renewable energy sources (RES)	11. Install solar PV systems	Installation of PV panel system with a capacity of 8.3 kWh/m^2 [12, 23].
		12. Install geothermal system	Installation of a geothermal heat pump for heating and cooling load. Proposed energy reduction: 50% of the building energy demand [12, 23].

1

2 3.3. Results and discussions

3 3.3.1. LOB prototypes

4 In summary, the construction year, window-wall (W/W) ratio and the number of floors
5 are identified as the KPIs of LOB in Shanghai, which are then used to classify LOB
6 into four prototypes based on the Chinese building codes and standards. Kindly see
7 Section S3 (supporting document) for brief details of the LOB prototypes (hereby
8 represented as LOP). The LOP are:

- 9 LOP1: LOB with W/W ratio between 0.2 – 0.4 and 5 floors built before 2005 (C1);
10 LOP2: LOB with W/W ratio < 0.2 and 3 floors built between 2006 – 2015 (C2);
11 LOP3: LOB with W/W ratio > 0.4 and 4 floors; built between 2006 – 2015 (C2);
12 LOP4: LOB with W/W ratio > 0.4 and 6 floors built between 2006 – 2015 (C2).

13 3.3.2 Building performance based on the individualistic retrofit measures

14 Table 3 presents the simulation result summarizing the building performance for the
15 individual retrofit measures on the four LOP (A more detailed result is presented in
16 Section S4 (supporting document), which includes the energy (total electricity
17 consumption), environmental (CO₂ emission) and economic (IC, annual electricity cost
18 savings and PBP) implications). It is noteworthy that the environmental impact
19 (reduction in CO₂ emission) is commensurate to the energy impact (reduction in total

electricity consumption). Besides, given that the capacity of the geothermal system is fixed, its impact (in percentage) is parallel across all the LOP.

Overall, the result reveals that the adopted retrofit measure is instrumental to the 3E outcome of the building (Fig. 2-4). Expectedly, the variation in energy consumption is due to the distinct building areas. Nonetheless, a significant distinction is witnessed in the energy consumption of LOP2 and LOP3, despite having similar building areas. This variation can be attributed to the larger W/W ratio of LOP3, which has a higher likelihood of imparting a large energy implication depending on the building geometry [36, 37].

Concerning the energy impact of the retrofit measures (Fig. 2), each measure significantly reduced the building's energy consumption, except for natural ventilation that showed approximately 1 – 3% reduction depending on the prototype. Specifically, prototypes within the C2 construction period (LOP2, LOP3 and LOP4) displayed an energy reduction > 2% in comparison to the *ca.* 1% reduction in LOP1. Other measures that displayed a greater energy impact in C2 than in C1 prototypes are the energy-conserving behaviours (changes in occupancy regimes and comfort requirements). Concerning changes in occupancy regimes, *ca.* 10 – 13% energy reduction was witnessed in the C2 prototypes, whereas *ca.* 10% reduction was depicted in LOP1. Likewise, a greater energy reduction potential (about 7 – 10%) was witnessed in the C2 prototypes in comparison to the *ca.* 5% reduction potential in LOP1 when changes in the comfort requirements are implemented. These results confirm the beneficial role of building characteristics (which is more upgraded in C2 buildings) in supporting passive retrofit measures. For instance, the impact of an upgraded ventilation system is reinforced by the low infiltration rate in C2 prototypes. The same principle applies to the energy-conserving behaviours, which when supported by the more efficient building systems and envelopes of C2 prototypes tends to promote a better energy performance than the C1 prototype. As a result, a higher energy impact is experienced in the C2 prototypes than in C1.

1 Table 3. Building performance result for the individual retrofit measures. (Building areas for LOP1 = 8,937.5 m²; LOP2 = 1,665 m²; LOP3 = 1,632
2 m² and LOP4 = 10,854 m²)

Retrofit measures	Impact on electricity (%)*				Initial investment cost (RMB)				Payback period (Years)			
	LOP1	LOP2	LOP3	LOP4	LOP1	LOP2	LOP3	LOP4	LOP1	LOP2	LOP3	LOP4
1. Occupancy regimes	10.06	12.73	12.73	10.36	12,691	2,364	2,317	15,413	0.1	0.1	0.1	0.1
2. Comfort requirements	4.68	9.11	8.71	7.80	56,306	10,490	10,282	68,380	0.9	0.6	0.5	0.6
3. Natural ventilation	1.01	2.08	3.27	3.26	3,575	666	653	4,342	0.3	0.2	0.1	0.1
4. Upgrade lighting	19.91	17.75	17.55	15.96	268,125	49,950	48,960	325,620	1.0	1.6	1.2	1.2
5. Upgrade HVAC	13.43	10.10	10.96	10.36	1,117,188	208,125	204,000	1,356,750	6.4	11.4	8.4	9.4
6. Insulate ceilings	13.06	3.32	2.19	3.32	143,894	26,807	26,275	174,749	0.8	4.5	5.4	3.8
7. Insulate walls	11.62	7.47	5.65	6.67	427,461	237,222	164,053	514,879	2.8	17.6	13.1	5.5
8. Insulate cool roofs	12.76	7.37	5.28	6.79	32,461	10,079	7,409	32,851	0.2	0.8	0.6	0.3
9. Upgrade Windows	13.55	7.37	8.26	9.85	190,487	63,152	134,885	403,627	1.1	4.7	7.3	2.9
10. Air-tightness	17.18	17.42	6.70	10.16	55,500	18,400	39,300	117,600	0.2	0.6	2.6	0.8
11. Solar/PV system	1.26	2.81	1.68	1.19	94,738	29,415	21,624	95,877	6.4	2.1	1.6	1.1
12. Geothermal system	50.00	50.00	50.00	50.00	2,037,750	379,620	372,096	2,474,712	3.1	4.2	3.7	3.9

3 * The total electricity consumption (in MWh) for the original (without retrofits) LOP1, LOP2, LOP3 and LOP4 are 1181.6, 164.03, 201.6 and 1266.8, respectively; with a corresponding EUI of
4 132.20 kWh/m², 98.52 kWh/m², 123.53 kWh/m² and 116.71 kWh/m², respectively
5

Regarding other measures (except for the RES), a greater energy reduction was witnessed in LOP1 than the LOP2, LOP3 and LOP4 prototypes. This variation is expected and is related to the age of the building. The building facades and facilities of LOP1 are more outdated than that of the C2 prototypes, and as a result, are more energy inefficient. Consequently, an upgrade in these building features will offer a more significant impact on the LOP1 prototype. Moreover, it is evident from Fig. 2 that the upgrade in lighting system and air-tightness are the most impactful measures across most LOP. Aside from these measures, altering the occupancy regime and upgrading the HVAC system also displayed good impact on energy reduction. Hence, the retrofit solution should include these measures with high energy-saving (and CO₂-saving) potential. However, this might not be the case from an economic perspective as some of these measures are relatively expensive and with low energy reduction impact per installation cost. Hence, further consideration of the optimal retrofit strategy should include cost indicators such as the IC and PBP.





Fig. 2. Energy reduction impact of retrofit measures on each prototype.

About economic implication, two cost indicators (IC and PBP) are assessed with insights into China's retrofit price and market structure (Table 3). Fig 3 shows the IC variation for each retrofit measure and it indicates that aside from the high installation cost of geothermal systems, upgrading the HVAC system is also cost demanding. The average IC (million RMB) for these measures across the four prototypes is 1.32 and 0.72, respectively. Other measures with relatively high costs are the upgrade in building envelopes (walls and windows with an average of RMB 0.34 million and RMB 0.20 million, respectively) and lighting (average of RMB 0.17 million). Expectedly, the least expensive measures are the passive strategies, including an upgrade in natural ventilation (av. RMB 2,300) and changes in occupancy regimes (av. RMB 8,200).

- 1 Overall, the retrofitting price is higher in LOP1 and LOP4 than in LOP2 and LOP3.
- 2 This is associated with the large building area.



3
4 Fig. 3. Initial investment costs of retrofit measures on each prototype.

5 Moreover, to evaluate the most impactful retrofit measure on an economic scale, a
6 combination of the energy and economic implications is necessary. On this account, the
7 PBP, which combines the annual savings (the energy cost saved within a year = energy
8 reduced by measure x electricity price (870 RMB/MWh)) and the IC is crucial. The
9 PBP identifies the most cost-beneficial measures as it refers to the time frame required
10 for the annual savings to offset the IC. The most beneficial measure will be that with
11 the lowest PBP, which is of utmost importance to investors as it relates to the quickest
12 return on investment. Fig. 4 shows the PBP for each measure, as presented in Table 3.

13 Fig. 4 shows that changes in occupancy regime (average of 0.1 years) and natural
14 ventilation (average of 0.2 years) demonstrated the shortest PBP, while HVAC system
15 (average of 8.9 years) and upgrade in wall insulation (average of 9.8 years) displayed
16 the longest PBP. The variation results from the varying offset of IC against the annual
17 savings. About short PBP, some of the measures do not show a significant impact on
18 building energy. For instance, natural ventilation and roof insulation displayed an
19 average PBP of 0.2 years and 0.5 years but exhibited an average energy reduction of
20 2.41% and 8.05%, respectively. This goes to elucidate the meagre energy impact of
21 some measures that are cost-beneficial. To attain the objective of a low energy target
22 for LOB in Shanghai, the most suitable retrofit solution should consider measures with
23 high energy reduction impact and low PBP.




Fig. 4. Payback period of retrofit measures for each prototype. In the above context, Fig. 5 presents an overall representation of the economic and energy (or environmental) impact for each retrofit measure. In this form, there is clarity about measures that can suitably provide high energy reduction impact and low PBP for each LOP. Here, the size of the bubbles indicates the magnitude of the energy reduction impact, while the y-axis represents the corresponding PBP. Therefore, the most suitable retrofit strategy should include measures with large bubble size and positioned at the lowest level of the PBP-axis. From Fig. 5, these conditions are observed by measures 1, 4 and 8 (representing changes in occupancy regime, lighting and roof insulation, respectively) for all LOP.

Besides, measure 2 (changes in comfort requirement) satisfies these conditions for the recent prototypes (LOP2, LOP3 and LOP4); while measure 6 (ceiling insulation upgrade) was only observed to satisfy these conditions in the aged LOP (LOP1). This variation is logical given that upgrade in the building envelope/façade should be more impactful on older buildings. Moreover, the impact of adjusting the comfort requirements is reinforced by the presence of an efficient building envelope/façade (as in the case of recent buildings). Furthermore, Fig. 5 depicts that measure 10 (air-tightness upgrade) is beneficial for all prototypes except LOP3. This can be ascribed to the high W/W ratio of LOP3 and the associated high cost for the air-tightness of the windows. Similarly, measure 3 (natural ventilation) was more impactful for LOP3 and LOP4. Also, this effect is attributed to the high W/W ratio, which is beneficial for promoting natural ventilation in buildings.




Fig. 5. Schematic comparison of the energy impact of each retrofit measure and their corresponding PBP for (a) LOP1, (b) LOP2, (c) LOP3, and (d) LOP4 prototypes. (Refer to Table 2 for the description of the retrofit measures notations)

In summary, each retrofit measure demonstrates varying impact on the different LOP. Hence, a trade-off between the 3E implications is required in selecting the most suitable retrofit solution. Overall, the upgrade in occupancy regime, lighting efficiency and roof insulation are the most impactful measures, given their reasonably high energy reduction impact and low PBP. Other cost-effective and beneficial measures include comfort requirement adjustment and upgrade in ceiling insulation, air-tightness and natural ventilation. An integral strategy incorporating these measures will proffer a suitable retrofit solution for LOB in Shanghai. However, a critical 3E assessment of all possible combinatorial retrofit strategies is necessary.

3.3.3. Building performance based on the combinatorial retrofit measures

After assessing the impact of all individual measures, the possible combinations of the measures are assessed using simplified mathematical equations. In this study, the simplified LCC evaluation only considers the initial investment costs (IC) and annual energy costs (EC) among various cost elements for the LCC formulation. This is due to the unavailability of data in China for other cost elements and the negligible costs for building maintenance and operation during a building life span. The IC includes all costs for retrofitting such as materials, labors and equipment while the EC is the average electricity cost. Details of the simplified numerical equations are presented in Section S1 (supporting document) and are based on related literature [8, 12].


With the 12 selected retrofit measures, there are 2^{12} (4096) possible combinations for each building. However, given the relevance of the solar/PV system as a relatively low-cost RES with a substantial reducing potential of environmental impact, this system is incorporated into all possible combinations. Therefore, 2^{11} (2,048) possible combinations are considered in this study. Fig. 6 shows the computed LCC (or total cost, TC), EC and IC profiles for LOP1 (Fig. 6 (a)), LOP2 (Fig. 6 (b)), LOP3 (Fig. 6 (c)) and LOP4 (Fig. 6 (d)). The raw data for the LCC, EC, IC and DL is presented in Section S5 (supporting document). The generated LCC profiles for LOP1, LOP2, LOP3 and LOP4 correspond with the trendline with an R^2 value of 0.8351, 0.7758, 0.8726, and 0.9053, respectively. The EC and IC trendlines for each LOP also exhibited a reasonably high R^2 value (> 0.84). As observed in Fig. 6, the prototypes with no retrofit measure (DL = 0%) has a zero IC and maximum EC. Contrarily, the strategy that combines all the retrofit measures (DL = 100%) displayed the maximum IC and lowest EC. The LCC_{min} value is situated between these two boundaries.

- Identifying the optimal retrofit solution

One of the key objective function for selecting an optimal retrofit solution is to identify the LCC_{min} . From Fig. 6, LCC_{min} is attained at DL values of about 99.10%, 84.92%, 88.72% and 84.65% for LOP1, LOP2, LOP3 and LOP4, respectively. The corresponding TC, IC and energy reduction is presented in Table 4. The energy reduction is synonymous to the EC reduction. Approximately 89%, 74%, 78% and 71% reduction in EC was observed for LOP1, LOP2, LOP3 and LOP4, respectively at the LCC_{min} from an initial EC value (million RMB) of 33.8, 5.4, 6.5 and 40.3 (using the EC profile, Fig. 6).

The results confirm that the optimal retrofit solution for C1 buildings (LOP1) requires a higher degree of upgrade (denoted by the DL value) than the C2 buildings. Besides, LOP1 and LOP4 require higher IC to attain the optimal status due to their large building areas. LOP4 exhibited a higher IC than LOP1 due to the significant distinction in the retrofit prices for (1) the HVAC and geothermal systems (associated with larger building area), and (2) the window upgrade and air-tightness improvement (associated with larger W/W ratio). These findings highlight the impact of building features on building retrofitting projects and its associated IC [36, 38].

For each building prototype, a number of combined retrofit solutions were identified to satisfy the LCC_{min} values. Using the DL values at LCC_{min} , a total of 8, 12, 5 and 23 combined retrofit solutions were identified for LOP1, LOP2, LOP3 and LOP4 buildings, respectively (Section S6, supplementary document). By evaluating the total equivalent CO_2 saved of these identified combined solutions (Fig. 7), the solution with the optimal 3E benefits is identified as that with the maximum CO_2 savings. Fig. 7 shows that the retrofit solutions with numbers 3, 12, 2 and 6 offer the maximum CO_2 savings at LCC_{min} for LOP1 (Fig. 7 (a)), LOP2 (Fig. 7 (b)), LOP3 (Fig. 7 (c)) and LOP4 (Fig. 7 (d)), respectively. Further descriptions of these retrofit solutions are presented in Table 5.



1 Fig. 6. Life cycle cost evaluation to determine the minimum LCC (or TC), and the
2 retrofit development level required to achieve the set EUI targets for (a) LOP1, (b)
3 LOP2, (c) LOP3, and (d) LOP4. (TC = total cost, EC = Energy cost, IC = Investment
4 cost)

1 Table 4: Summary of deduced outcomes of the retrofit solutions to achieve the minimum LCC and the set EUI targets for each LOP. (Values are
2 deduced from the respective profiles from Fig. 6)

Building Prototype	Original EUI (kWh/m ²)	At minimum LCC					At 85 kWh/m ²			At 70 kWh/m ²		
		TC ^a (x10 ⁶ RMB)	DL ^b (%)	IC ^c (x10 ⁶ RMB)	ER ^d (%)	EUI (kWh/m ²)	DL ^b (%)	IC ^c (x10 ⁶ RMB)	ER ^d (%)	DL ^b (%)	IC ^c (x10 ⁶ RMB)	ER ^d (%)
LOP1	132.20	12.4	99	4.2	89	13.69	38	2.0	36	47	2.3	47
LOP2	98.52	2.4	85	1.0	74	25.54	12	0.3	14	27	0.4	30
LOP3	123.53	2.7	89	0.9	78	25.14	37	0.4	31	50	0.5	43
LOP4	116.71	16.4	85	4.5	71	35.25	31	2.1	27	47	2.5	40

3 ^aTC = total cost or life cycle cost at minimum LCC obtained via the TC profile,

4 ^bDL = retrofit development level required to attain the set targets (LCC_{min} or EUI targets). Read off from the x-axis,

5 ^cIC = initial investment cost corresponding to the required DL. Read off from the IC profile,

6 ^dER = energy reduction computed from $\frac{EC_{original} - EC_{retrofit}}{EC_{original}} \times 100\%$, where EC_i = energy cost or $\frac{E_{original} - E_{retrofit}}{E_{original}} \times 100\%$, where E_i = annual energy
7 consumption.

8




Fig. 7. LCC_{min} and environmental evaluation depicting the optimal retrofit solution with maximum CO₂ savings for (a) LOP1, (b) LOP2, (c) LOP3, and (d) LOP4.

Table 5. Summary of the selected combination of retrofit solutions for the proposed prototypes. (For macro-scale intervention at LCC_{min}: the primary retrofit measures are those selected by all four prototypes, while the secondary measures are required by three of the prototypes.)

Measures	LCC _{min}				85 EUI target ⁺	70 EUI target*	
	LOP1	LOP2	LOP3	LOP3		A	B
1. Occupancy regimes	✓	✓	✓	✓			
2. Comfort requirements		✓	✓	✓	✓	✓	✓
3. Natural ventilation	✓	✓	✓	✓			
4. Energy-efficient lighting	✓				✓	✓	✓
5. Energy-efficient HVAC	✓	✓	✓	✓	✓	✓	✓
6. Insulate ceilings	✓			✓	✓	✓	
7. Insulate walls	✓	✓	✓		✓	✓	✓

8. Insulate cool roofs	✓	✓	✓	✓	✓	✓	✓
9. Energy-efficient Windows	✓		✓	✓			✓
10. Air-tightness	✓	✓		✓			
11. Install solar PV systems	✓	✓	✓	✓			
12. Install geothermal system	✓	✓	✓	✓			

⁺Applies to all LOB prototypes

^{*}A applies to LOP2 and LOP3 prototypes, while B applies to LOP1 and LOP4 prototypes

- Identifying the suitable retrofit solution to achieve the set EUI targets

Concerning the regulated standards, Fig. 6 also indicates the minimal upgrade requirements to attain the 70 EUI and 85 EUI target in each prototype. Overall, the EUI at optimal status is significantly lesser than that of the regulated standard, 70 - 85 kWh/m². A reduction of the original EUI values (Table 4) to the 70 kWh/m² and 85 kWh/m² targets will require a matching decrease in the EC values. The required upgrades necessary for this reduction were obtained by reading off the DL values that corresponds to the EC obtainable at the EUI targets. At the 70 kWh/m² target, the matching EC (million RMB) for LOP1, LOP2, LOP3 and LOP4 are estimated as 17.9, 3.8, 3.7 and 24.2, respectively; whereas for the 85 kWh/m² target, the EC (million RMB) are 21.7, 4.7, 4.5 and 29.4, respectively.

Using these EC values, the DL required to attain the 70 kWh/m² and 85 kWh/m² target for LOP1, LOP2, LOP3 and LOP4 are obtained (Table 4). Expectedly, LOP2 required the least level of upgrade to attain the set EUI targets owing to its small building area and W/W ratio, which are part of the major factors to be highly considered in any retrofit project. With the DL values, the IC required to achieve the set EUI targets is obtained (Table 4). Subsequently, the probable combinatorial retrofit solutions with an IC above the required IC value are selected for further process.

For example, Table 4 shows that the DL values of ca. 47.2% (for 70 kWh/m²) and 37.5% (85 kWh/m²) require an IC value of ca. RMB 2.4 million and RMB 2.0 million, respectively for LOP1. Above this required IC values, a total of 1332 retrofit strategies are identified. Using the AHC module of XLSTAT (version 2019.3.2) software, the strategies are partitioned into 3 clusters, with a centroid strategy that represents each cluster. The centroid strategy serves as the average primary strategy for the clustered class of strategies. A summary of the cluster analysis result is presented in Table 6. The combinatorial retrofit strategy comprising of adjusting comfort requirement, upgrade of lighting and HVAC systems, improved insulation of the building walls, roofs and windows, and PV installation is the major centroid strategy to achieve the 70 kWh/m². This centroid strategy (denoted as strategy 25) represents 1319 (out of 1332) clustered

strategies. On the other hand, an integrated adjustment of the comfort requirement, upgrade of lighting and HVAC systems, improved insulation of the building ceilings, walls and roofs, and PV installation is the major centroid strategy to achieve the 85 kWh/m². This centroid strategy is denoted as strategy 238, which represents 1079 (out of 1091) clustered strategies.

Concerning LOP2, the lower IC value at the set EUI targets (Table 4) can be attributed to the smaller building area and its recent construction age (when compared to that for LOP1 model). With these requirements, 1668 and 1865 combinatorial retrofit strategies were identified to achieve the 70 and 85 EUI targets, respectively. The cluster analysis (Table 6) reveals that the combinatorial retrofit solution comprising of adjustment of the comfort requirement, upgrade of lighting and HVAC systems, improved insulation of the building ceilings, walls and roofs, and PV installation is the major centroid strategy for attaining the set EUI targets. For the 70 kWh/m², this strategy (denoted as strategy 774) represents 1654 (out of 1668) strategies, whereas the same strategy (denoted as strategy 971) represents 1853 (out of 1865) strategies for the 85 kWh/m².

For LOP3, the relative increase in IC (required to attain the 70 EUI and 85 EUI targets, Table 4) when compared to LOP2 can be ascribed to the difference in W/W ratio notwithstanding the smaller building area of LOP3. Using these values, 1021 and 1446 combinatorial retrofit strategies were identified to achieve the 70 and 85 EUI targets, respectively. The cluster analysis reveals that the centroid strategy for both EUI targets for LOP3 has the same combinatorial retrofit solution as that of LOP2. For the 70 kWh/m², the major centroid strategy is denoted by strategy 140 which represents 1009 (out of 1021) strategies, whereas this strategy is denoted by strategy 345 which represents 1432 (out of 1446) strategies for the 85 kWh/m² (Table 6).

Likewise for LOP4, 1096 and 1476 combinatorial retrofit strategies were identified to achieve the 70 and 85 EUI targets, respectively based on the DL and IC values (Table 4). Remarkably, the major centroid strategy for both 70 and 85 EUI targets have the same combinatorial retrofit measures as that for LOP1. For the 70 kWh/m², the centroid strategy is indicated as strategy 59, which represents 1084 (out of 1096) clustered strategies. On the other hand, the major centroid strategy (strategy 331) for the 85 kWh/m² represents 1464 (out of 1476) clustered strategies (Table 6).

A summary of the retrofit solutions identified in this study is presented in Table 5. In summary, it is noted that an integral retrofit strategy consisting of adjustment in comfort requirement, upgrade of lighting, HVAC and building envelope (walls, roofs and ceilings), and PV installation is common for attaining the EUI targets across all prototypes (on a macro-scale). The only exception is that upgrade of windows rather than ceilings is included to attain the 70 EUI target for LOP with large building areas and relatively high W/W ratio (LOP1 and LOP4). This distinction in the results is logical given that a more beneficial trade-off between the energy and economic

implication is likely in buildings with large building area and W/W ratio when the air-tightness and energy-efficiency of the windows are upgraded [37]. Similarly, the macro-scale analysis presents that the primary measures (as itemized in Table 5) necessary for attaining an optimal energy performance for all LOB stocks in Shanghai should include adjustments in occupancy regime, upgrade of HVAC and natural ventilation, improvement of cool roofs and installation of solar/PV and geothermal systems. Other necessary measures (but dependent on the building characteristics) include adjustments in comfort requirements, wall insulations, upgrade of windows and air-tightness.

Table 6. Cluster analysis of retrofit strategies to achieve the 70 and 85 EUI building targets. Full description of all combinatorial retrofit strategy and their respective dendrograms for each EUI target are presented in Sections S7 and S8 (supporting document), respectively.

LOB model	Cluster Class	85 EUI Target		70 EUI Target	
		Centroid strategy	No. of strategies	Centroid strategy	No. of strategies
LOP1	1	238	1319	25	1079
	2	1304	12	1063	11
	3	1332	1	1091	1
	Total		1332		1091
LOP2	1	971	1853	774	1654
	2	1845	11	1648	13
	3	1865	1	1668	1
	Total		1865		1668
LOP3	1	345	1432	140	1009
	2	1430	13	1005	11
	3	1446	1	1021	1
	Total		1446		1021
LOP4	1	331	1464	59	1084
	2	1452	11	1072	11
	3	1476	1	1096	1
	Total		1476		1096

3.4 Validation on a typical building

First, an empirical approach was adopted to validate the simulation results. Here, the simulation results were compared with actual metered data for a typical building representing the LOP2 prototype (Bldg #60 in Hong Xing Int'l Square, No. 1969 Puxing Rd, Shanghai, see Fig. 8a). Comparatively, the simulated result is within a $\pm 5\%$ error margin of the actual data. Following the empirical validation, it is also essential

to verify the outcome of the retrofit solutions proposed by the combined simulation and numerical analysis. In details, the proposed retrofit solutions were simulated on the above mentioned typical building to confirm the outcomes after retrofitting. Table 7 summarises the retrofit solutions and outcomes proposed to attain the required EUI target (85 kWh/m²) and the LCC_{min} requirement. Excluding the RES, the other measures, as presented in Table 7, are inputted into the IES-VE building model (Fig. 8b) to validate the annual energy and CO₂ emission savings.

Table 7. Proposed retrofit solution for the case study building LOP2.

Activity	LOP2	
	85 EUI target	Min. LCC
1. Occupancy regimes (Monitoring strategies)		✓
2. Comfort requirements	✓	✓
3. Natural ventilation		✓
4. Energy-efficient Lightings	✓	
5. Energy-efficient HVAC	✓	✓
6. Insulate ceilings	✓	✓
7. Insulate walls	✓	✓
8. Insulate cool roofs	✓	
9. Energy-efficient windows		
10. Air-tightness		✓
11. Install solar PV systems*		✓
12. Install geothermal system ⁺		✓
Energy reduction (%)	14%	74%
Annual CO ₂ saved (Gg)	-	0.1062

*Solar/PV system capacity = 8.3 kWh/m² (~4.61 MWh)

⁺Geothermal system produced 50% (~82.02 MWh) of the building energy demand



Fig. 8. (a) Original building and (b) IES-VE model representing LOP2 prototype for

case study analysis.

3.4.1. 85 EUI target

Table 8 presents the simulated energy performance after implementing the proposed retrofit solution for the 85 EUI target. After retrofitting, the building energy reduced from the original 164.03 MWh (Section S4) to 141.64 MWh (13.65% reduction), which corresponds to a final EUI of 85.07 kWh/m² with a matching 20% reduction in CO₂ emission to 73,513 kg CO₂.

Comparatively, this depicts that the outcome of the proposed model is reliable with a 0.1% error margin. Hence, it is evident that integrating the adjustment of occupants' comfort level and upgrade of HVAC, lighting, ceilings, walls and roofs with a total initial investment of RMB 0.54 million is suitable to achieve the required EUI target for LOP2. However, given the electricity price of 870 RMB/MWh, the estimated PBP will be longer than 20 years.

Table 8. Validation result for the EUI 85 target

Date	Electricity (MWh)	Carbon Emission Kg-CO ₂
Jan 01-31	17.37	9013
Feb 01-28	13.28	6892
Mar 01-31	8.66	4494
Apr 01-30	5.38	2791
May 01-31	8.88	4609
Jun 01-30	13.21	6856
Jul 01-31	18.86	9787
Aug 01-31	18.50	9599
Sep 01-30	13.29	6898
Oct 01-31	6.87	3564
Nov 01-30	6.07	3149
Dec 01-31	11.29	5860
Summed total	141.64	73513

3.4.2. Minimum LCC

At LCC_{min}, the optimal retrofit strategy (with an estimated energy reduction of 74%) was defined as a combination of nine individual retrofit measures: seven energy-conserving measures and two energy-producing (RES) measures. However, given the challenge of simulating energy-producing measures with IES-VE, the RES was excluded in the simulation process and their impact was validated mathematically. Here, a two-step approach is employed to simplify the validation process.

Step 1: Simulation of the seven energy-conserving measures

Table 9 illustrates the simulated energy behaviour after retrofitting with the seven energy-conserving measures. Without the RES, the simulated building energy

(electricity) demand (BEC_s) is 115.76 MWh (29.42% reduction). Similarly, CO_2 emission reduced from 91,361 kg- CO_2 to 60,081 kg- CO_2 . This environmental outcome (annual CO_2 -savings = 0.0313 Gg- CO_2) is much lesser than that proposed by the model framework (0.1062 Gg- CO_2). This result verifies that the arithmetic sum of the CO_2 savings from the individual retrofit measure does not accurately predict the actual CO_2 emission behaviour. A probable reason for this distinction will be the synergistic effect resulting from the integration of the individual measures.

Table 9. Validation result at LCC_{min}

Date	Electricity (MWh)	Carbon Emission Kg- CO_2
Jan 01-31	9.93	5152
Feb 01-28	7.49	3885
Mar 01-31	6.02	3124
Apr 01-30	5.38	2791
May 01-31	9.44	4897
Jun 01-30	12.36	6416
Jul 01-31	16.43	8529
Aug 01-31	16.33	8477
Sep 01-30	12.37	6419
Oct 01-31	7.76	4026
Nov 01-30	5.38	2792
Dec 01-31	6.88	3571
Summed total	115.76	60081

Step 2:

Considering the RES, the solar/PV and geothermal systems have fixed energy capacities of 4.61 MWh ($EP_{Solar/PV}$) and 82.02 MWh ($EP_{Geothermal}$), respectively. Assuming these are accurately simulated in the software, then the resultant building energy demand (BEC_r) after retrofitting with the nine measures is:

$$BEC_r = BEC_s - (EP_{Geothermal} + EP_{Solar/PV}) \quad (12)$$

$$= 115.76 - (82.02 + 4.61) \text{ MWh}$$

$$= 29.13 \text{ MWh}$$

Relative to the original model, there is an 82.24% energy reduction at LCC_{min} , which bears a close match with that predicted by the model framework by ~90%. In summary, the retrofit solutions for attaining the set EUI target and LCC_{min} are likely to reach their designated objectives. As such, the model framework is proven to be reliable. However, a more accurate assessment approach is required for predicting environmental implication.

3.5. Decision based on the investor type

Using the deciding criteria discussed in Section 2.2.5, Fig. 9 presents a comparison of the computed EUI:LCC percentage ratios of the respective DL, IC and ER at the stipulated EUI targets. The computed values are tabulated in Section S9 (supporting document).

For the 85 EUI target, Fig. 9 shows that $\%IC_{EUI:LCC} > \%ER_{EUI:LCC}$ for all LOP. This result indicates that a relatively higher IC is required by the retrofit solution (for the EUI target) to achieve a commensurate energy reduction to that at LCC_{min} . On this account, applying the retrofit solution for the LCC_{min} is more suitable in *scenario 1*. In *scenario 2*, $\%DL_{EUI:LCC} < \%ER_{EUI:LCC}$ for all prototypes except for LOP3. Here, a relatively lower degree of retrofit development is required to achieve a proportional energy reduction when compared to that at LCC_{min} . Therefore, it is suggested that the retrofit solution for the EUI target is more suitable for LOP1, LOP2 and LOP4; whereas the optimal retrofit strategy is recommended for LOP3.

About *scenario 1* for the 70 EUI target, the LCC retrofit solution is more appropriate for LOP1 and LOP3 ($\%IC_{EUI:LCC} > \%ER_{EUI:LCC}$). Contrarily, the 70 EUI retrofit solution is considered to be more suitable for LOP2. Lastly, the LOP4 model displayed $\%IC_{EUI:LCC} = \%ER_{EUI:LCC}$. In this case, the matching $\%DL_{EUI:LCC}$ is compared with $\%ER_{EUI:LCC}$ as an additional condition. The results depict that $\%DL_{EUI:LCC} < \%ER_{EUI:LCC}$, and as such, the 70 EUI retrofit solution is recommended. About *scenario 2*, the EUI retrofit solution is more suited for all LOP ($\%DL_{EUI:LCC} < \%ER_{EUI:LCC}$) except for LOP3.




Fig. 9. Ratios of LCC outcomes (DL, IC and ER) achieved by each EUI targets.

4. Conclusion and limitations

Given the importance of upgrading buildings amidst urban development, this study provides a **coordinated multi-layer** evaluating model for assessing retrofit alternatives on a macro-scale. The model proposes a comprehensive approach that integrates a data

1 mining procedure into the decision-making process to provide a simple and holistic
2 (energy, environmental and economic (3E)) assessment of building retrofits. Also, the
3 approach provides a methodological contribution that enables decision-makers to select
4 the most reasonable retrofit solution by defining rational decision criteria based on the
5 set performance targets.

6 The model framework consists of three methodological models: building stock
7 aggregation model, individualistic 3E model, and a life cycle cost (LCC)-environmental
8 assessment model. The efficacy of the framework is demonstrated and validated using
9 a case study analysis of achieving the set Chinese EUI targets for low-rise office
10 buildings (LOB) in Shanghai. The case study results identify four prototypical buildings
11 and 12 commonly applied retrofit measures (both active and passive, varying from low
12 to high-cost efforts) for existing LOB in Shanghai.

13 Independently, the different retrofit measures displayed varying 3E implications.
14 However, a larger energy reduction impact was witnessed on buildings built before
15 2005 (C1) than on that built after 2005 (C2) when active measures are implemented.
16 On the contrary, passive measures displayed a greater energy impact on C2 than on C1
17 buildings. Overall, the upgrade in lighting efficiency and air-tightness improvement are
18 the most impactful measures across most of the buildings.

19 Jointly, 2,048 possible combinations of retrofit solutions are assessed for optimal
20 building performance and to achieve the set EUI performance targets based on the 3E
21 concerns. By employing a clustering approach and the results of the individualistic
22 retrofit analysis as input sensitivity data, the numerous solutions are streamlined to the
23 most likely macro-scale solution (combining the adjustment in comfort requirement,
24 upgrade of lighting, HVAC and building envelope (walls, roofs and ceilings), and PV
25 installation). Similarly, the result recommends that the primary retrofit measures to
26 attain an optimal building performance for all LOB stocks in Shanghai should include
27 adjustments in occupancy regime, upgrade of HVAC and natural ventilation,
28 improvement of cool roofs, and installation of solar/PV and geothermal systems. Other
29 necessary measures include adjustments in comfort requirements, upgrade of wall
30 insulations, windows and air-tightness.

31 Considering the benefits of achieving the EUI targets and optimal performance,
32 decision criteria based on the investors' priority was proposed to guide the selection on
33 which retrofit solution to implement. Based on this criteria, the optimal retrofit solution
34 is recommended for investors with investment cost as their primary priority. Contrarily,
35 the EUI retrofit solution is the most suited for investors focused on
36 environmental/energy concerns. Overall, the makeshift decision model offers investors
37 a framework to select reasonable retrofit solutions based on different performance
38 targets on a macro-scale.

Limitations and future considerations

Depending on the distinctive features of the city, building typology or size of building inventory, the obtained results for the case study could differ. To improve the proposed framework, larger database of building stocks, their characteristics and the retrofit alternatives should be considered, rather than on limited data for specific projects.

However, the present methodology is hyper-heuristic and can limit its application to small building inventories. The full scalable deployment of the methods faces a number of technical challenges that grow with the complexity of the involving algorithms. Thus, the original algorithms must often be fine-tuned to effectively use the distributed computational methods. Besides, the associated large data from large building stocks contains a considerable amount of outliers and is subject to high degrees of uncertainty, which will further complicate the analytical data processing. This issue of applicability can be addressed with the aid of computational intelligence techniques for big data analytics, particularly for the scalability of the clustering technique for big data.

For instance, undergoing study is focused on demonstrating the impact of a vast option of each retrofit measure on the optimal solution for the individualistic buildings (micro scale intervention). Besides, insights into the interactions between each measure could offer an informed decision on the optimal retrofit solution and could be more meaningful in a micro-scale analysis. For accurate scalability of the coordinated approach established in this study, a multi-stage successive refinement of the clustering technique, with each stage supervising the previous one is recommended [39]. This solution will offer a distributed and unsupervised learning algorithm suited for a coordinated methodology of this nature, which will also increase the processing efficiency and reduce the optimization time. Finally, using a real energy retrofit case study, the efficacy and applicability of the framework can be validated. Also, accounting for uncertainties via probabilistic criteria values will further enhance the model framework.

Moreover, in the LCC evaluation, other cost elements were not considered due to lack of data availability on the study period. Maintenance and operating costs, tax incentives and appropriate rebates could be considered as additional cost elements. This study only highlights how the LCC approach could be integrated into the model framework for building retrofits on a macro-scale intervention. Overall, the proposed approach remains valid for developing reliable retrofit solutions.

References

1. Zheng, L. and J. Lai, *Environmental and economic evaluations of building energy retrofits: Case study of a commercial building*. Building and Environment, 2018. **145**: p. 14-23.

- 1 2. Nägeli, C., et al., *A service-life cycle approach to maintenance and energy*
2 *retrofit planning for building portfolios*. Building and Environment, 2019.
3 **160**: p. 106212.
- 4 3. Rysanek, A. and R. Choudhary, *A decoupled whole-building simulation*
5 *engine for rapid exhaustive search of low-carbon and low-energy building*
6 *refurbishment options*. Building and Environment, 2012. **50**: p. 21-33.
- 7 4. Chidiac, S., et al., *A screening methodology for implementing cost effective*
8 *energy retrofit measures in Canadian office buildings*. Energy and Buildings,
9 2011. **43**(2-3): p. 614-620.
- 10 5. Shao, Y., P. Geyer, and W. Lang, *Integrating requirement analysis and multi-*
11 *objective optimization for office building energy retrofit strategies*. Energy and
12 Buildings, 2014. **82**: p. 356-368.
- 13 6. Wang, B. and X. Xia, *Optimal maintenance planning for building energy*
14 *efficiency retrofitting from optimization and control system perspectives*.
15 Energy and Buildings, 2015. **96**: p. 299-308.
- 16 7. Roberti, F., et al., *Energy retrofit and conservation of a historic building using*
17 *multi-objective optimization and an analytic hierarchy process*. Energy and
18 Buildings, 2017. **138**: p. 1-10.
- 19 8. Jafari, A. and V. Valentin, *Selection of optimization objectives for decision-*
20 *making in building energy retrofits*. Building and Environment, 2018. **130**: p.
21 94-103.
- 22 9. Zheng, D., L. Yu, and L. Wang, *A techno-economic-risk decision-making*
23 *methodology for large-scale building energy efficiency retrofit using Monte*
24 *Carlo simulation*. Energy, 2019. **189**: p. 116169.
- 25 10. Zheng, D., et al., *A screening methodology for building multiple energy*
26 *retrofit measures package considering economic and risk aspects*. Journal of
27 Cleaner Production, 2019. **208**: p. 1587-1602.
- 28 11. Chen, X., et al., *Multi-Criteria Assessment Approach for a Residential*
29 *Building Retrofit in Norway*. Energy and Buildings, 2019: p. 109668.
- 30 12. Jafari, A. and V. Valentin, *An optimization framework for building energy*
31 *retrofits decision-making*. Building and Environment, 2017. **115**: p. 118-129.
- 32 13. Mauro, G.M., et al., *A new methodology for investigating the cost-optimality*
33 *of energy retrofitting a building category*. Energy and Buildings, 2015. **107**: p.
34 456-478.
- 35 14. Wang, B., X. Xia, and J. Zhang, *A multi-objective optimization model for the*
36 *life-cycle cost analysis and retrofitting planning of buildings*. Energy and
37 Buildings, 2014. **77**: p. 227-235.
- 38 15. Allacker, K., et al., *Energy simulation and LCA for macro-scale analysis of*
39 *eco-innovations in the housing stock*. The International Journal of Life Cycle
40 Assessment, 2019. **24**(6): p. 989-1008.

- 1 16. Lotteau, M., et al., *Critical review of life cycle assessment (LCA) for the built*
2 *environment at the neighborhood scale*. Building and Environment, 2015. **93**:
3 p. 165-178.
- 4 17. Mastrucci, A., et al., *Life Cycle Assessment of building stocks from urban to*
5 *transnational scales: A review*. Renewable and Sustainable Energy Reviews,
6 2017. **74**: p. 316-332.
- 7 18. Chastas, P., et al., *Normalising and assessing carbon emissions in the building*
8 *sector: A review on the embodied CO2 emissions of residential buildings*.
9 Building and Environment, 2018. **130**: p. 212-226.
- 10 19. Shen, P., et al., *Rapid multi-objective optimization with multi-year future*
11 *weather condition and decision-making support for building retrofit*. Energy,
12 2019. **172**: p. 892-912.
- 13 20. Hong, Y., et al., *Correlation between building characteristics and associated*
14 *energy consumption: Prototyping low-rise office buildings in Shanghai*.
15 Energy and Buildings, 2020. **217**: p. 109959.
- 16 21. Mohamad, I. and D. Usman, *Standardization and Its Effects on K-Means*
17 *Clustering Algorithm*. Research Journal of Applied Sciences, Engineering and
18 Technology, 2013. **6**: p. 3299-3303.
- 19 22. Crawley, D.B., et al., *Contrasting the capabilities of building energy*
20 *performance simulation programs*. Building and Environment, 2008. **43**(4): p.
21 661-673.
- 22 23. Jafari, A. and V. Valentin, *Decision-making life-cycle cost analysis model for*
23 *energy-efficient housing retrofits*. International Journal of Sustainable
24 Building Technology and Urban Development, 2015. **6**(3): p. 173-187.
- 25 24. Pistore, L., et al., *A stepwise approach integrating feature selection,*
26 *regression techniques and cluster analysis to identify primary retrofit*
27 *interventions on large stocks of buildings*. Sustainable Cities and Society,
28 2019. **47**: p. 101438.
- 29 25. Hong, Y., W. Deng, and C.I. Ezech, *Low-rise Office Retrofit: Prerequisite for*
30 *Sustainable and Green Buildings in Shanghai*. IOP Conference Series: Earth
31 and Environmental Science, 2019. **281**: p. 012025.
- 32 26. Hong, Y., et al., *Building Energy Retrofit Measures in Hot-Summer–Cold-*
33 *Winter Climates: A Case Study in Shanghai*. Energies, 2019. **12**(17): p. 3393.
- 34 27. MOHURD, *Standard for energy consumption of building GB/T 51161-2016*.
35 2016.
- 36 28. MOHURD, *Design standard for energy efficiency of public buildings*
37 *GB50189-2015*, Ministry of Housing and Urban-Rural Development of the
38 China, Editor. 2015: China.
- 39 29. CIBSE, *Energy Efficiency in Buildings: CIBSE Guide F Chartered Institution*
40 *of Building Services Engineers*. 2004, London: Chartered Institution of
41 Building Services Engineers.

- 1 30. Ma, Z., et al., *Existing building retrofits: Methodology and state-of-the-art.*
2 Energy and Buildings, 2012. **55**: p. 889-902.
- 3 31. Li, Y., et al., *The Existing Building Sustainable Retrofit in China-A Review*
4 *and Case Study.* Procedia Engineering, 2017. **205**: p. 3638-3645.
- 5 32. Hong, Y., et al., *Attaining sustainability in built environment: Review of green*
6 *retrofit measures for existing buildings.* IOP Conference Series: Earth and
7 Environmental Science, 2019. **227**: p. 042051.
- 8 33. MOHURD, *Public Building Energy Saving Design Standard, GB-50189.*
9 China National Code, 2005.
- 10 34. Papadopoulos, S., et al., *Rethinking HVAC temperature setpoints in*
11 *commercial buildings: The potential for zero-cost energy savings and comfort*
12 *improvement in different climates.* Building and Environment, 2019. **155**: p.
13 350-359.
- 14 35. Shao, F., *Case Study: Measurement and Analysis of Incremental Cost of*
15 *Green Buildings.* 2019:
16 <http://www.360doc2.net/wxarticlenew/805953636.html>.
- 17 36. Yeom, S., et al., *Determining the optimal window size of office buildings*
18 *considering the workers' task performance and the building's energy*
19 *consumption.* Building and Environment, 2020: p. 106872.
- 20 37. Troup, L., et al., *Effect of window-to-wall ratio on measured energy*
21 *consumption in US office buildings.* Energy and Buildings, 2019. **203**: p.
22 109434.
- 23 38. Kim, D., et al., *Net-zero energy building design and life-cycle cost analysis*
24 *with air-source variable refrigerant flow and distributed photovoltaic systems.*
25 Renewable and Sustainable Energy Reviews, 2020. **118**: p. 109508.
- 26 39. Ianni, M., et al., *Fast and effective Big Data exploration by clustering.* Future
27 Generation Computer Systems, 2020. **102**: p. 84-94.
- 28