

Integrated motor drives: state of the art and future trends

ISSN 1751-8660

Received on 5th October 2015

Revised on 18th December 2015

Accepted on 12th January 2016

doi: 10.1049/iet-epa.2015.0506

www.ietdl.org

Robert Abebe¹ ✉, Gaurang Vakil¹, Giovanni Lo Calzo¹, Thomas Cox¹, Simon Lambert², Mark Johnson¹, Chris Gerada¹, Barrie Mecrow²

¹Department of Electrical and Electronic Engineering, University of Nottingham, University Park, Nottingham, UK

²School of Electrical and Electronic Engineering, Newcastle University, Newcastle upon Tyne, UK

✉ E-mail: eextra18@nottingham.ac.uk

Abstract: With increased need for high power density, high efficiency and high temperature capabilities in aerospace and automotive applications, integrated motor drives (IMD) offers a potential solution. However, close physical integration of the converter and the machine may also lead to an increase in components temperature. This requires careful mechanical, structural and thermal analysis; and design of the IMD system. This study reviews existing IMD technologies and their thermal effects on the IMD system. The effects of the power electronics position on the IMD system and its respective thermal management concepts are also investigated. The challenges faced in designing and manufacturing of an IMD along with the mechanical and structural impacts of close physical integration is also discussed and potential solutions are provided. Potential converter topologies for an IMD like the matrix converter, two-level bridge, three-level neutral point clamped and multiphase full bridge converters are also reviewed. Wide band gap devices like silicon carbide and gallium nitride and their packaging in power modules for IMDs are also discussed. Power modules components and packaging technologies are also presented.

1 Introduction

Over the last two decades there has been a shift from traditional physically separated motor and drive systems to more compact, power dense, motor-drive combinations [1]. This new power-dense motor-drive structure combines both the motor and its associated control and drive circuitry within a single enclosure. The earliest records of commercially available motor-drive systems were manufactured by Grundfos in 1991 and Franz Morat KG in 1993 [2].

These compact systems have been called a variety of names from ‘smart motors’ to ‘integrated motors’, the latter forming the foundation for the new moniker currently identified with these systems [3]. The term ‘integrated motor drive (IMD)’ is the latest associated with this class of products and is as a result of the success of a TB Woods Inc. manufactured motor-drive registered under the same name [3].

IMDs are increasingly being developed and produced by machine manufacturers due to the significant potential benefits they offer. The most significant of these benefits include direct replacement of inefficient direct on line motors, increased power density, lower losses and lower costs compared with separate motor and drive solutions. Technological advancements over the last decade have led to the development of robust electronic components able to withstand the harsh environments required by some forms of integration [4]. By eliminating separate enclosures and long cable runs, the integrated approach promises to lower system costs by 20 to 40% [5].

Elimination of transmission cables has economic advantages, including increased reliability due to the removal of the output filter commonly required for long cables. Removal of long cable runs and integration into a single package will also significantly reduce potential electromagnetic interference (EMI). This allows for EMI testing and prevention measures to be applied to the overall package at the point of manufacture. The space requirement for a separate converter will be eliminated and overall system size may be reduced compared with a traditional separated solution [6, 7]. Commissioning and testing time can also be

potentially reduced by performance testing of the converter and machine as a single unit [6, 8, 9]. This will also eliminate the need for inverter control rooms and ventilation equipment as the integrated motor and drive can also utilise a singular cooling system, further reducing size and cost of the IMD compared with a separated solution [10]. Integrating the motor and drive will also allow for increased automation of the manufacturing process [11].

Various power electronic integration approaches have been proposed in the literature ranging from a simple mounting of the converter on the machine housing to high levels of modular integration.

To take advantage of the benefits of an IMD it is important to define what it is. For the purpose of this work – an IMD is the result of the functional and structural integration of the power electronics (PE) converter with the machine as a single unit taking into consideration the electrical and structural and thermal impacts both components have on each other and the system as a whole.

All IMD units fulfil the functional electrical integration of the PE with the machine, as this is a defining feature of an IMD. However, the structural integration is a design problem which requires careful mechanical and thermal analysis of the converter and machine as a single unit. This is a challenge for designing and manufacturing an IMD.

Despite the attractive benefits IMDs present, reservations still exist about their widespread use. A simple addition of PE to the machine adds volume to the combination if the structures are not properly physically integrated. Having the PE in close proximity to the machine (anywhere on or inside the housing) poses a thermal management problem for the entire system. Until recently, above 7.5 kW output, the effects of heating from both machine and drive build up significantly and present a practical limit for the manufacture of higher power drives [3, 6]. The physical size of the converter also limits the practical power rating of commercial IMD units up to the 7.5 kW limit. Commercialisation of higher power and larger size IMDs will require more complex designs and impact product costs [1, 4]. Above this 7.5 kW threshold, traditional separated motor-drive systems might offer a better




Fig. 1 Surface mount integration

a Simple addition of PE case on electric motor [21]

b Modularised converter units mounted on motor housing [22]

alternative hence the dearth in high power commercially available IMDs.

Unlike the machine, the PE converter and associate control electronics are rarely considered either mechanically or thermally robust. Without proper thermal management, placing the PE close to the machine (the prominent heat source) might cause irreparable damage to the drive. There are also problems of vibrations which could damage the internal electrical connections of the converter and decrease the expected PE lifetime. Limitations due to lack of available space in the motor and the need to adapt the power converter to the electromagnetic field stresses inside the motor housing also pose major issues.

This paper reviews existing IMD configurations based on the mounting position of the converter, the benefits they provide and the challenges they face. Converter topologies, converter packaging and existing passive technologies for IMDs are also presented

2 Principal types of IMD

Despite significant awareness of IMDs in industry, extensive research and literature on the topic, very little work exists on complete PE and machine integration. The majority of literature and research exists as reviews of present IMD technologies and

market perspective [12–16], finite element analysis (computer simulations) [17, 18] and functional integration [19].

Due to spatial restrictions for physical integration of PE on or inside the motor housing, the complete structural PE integration research and documentation can be divided into three major categories namely – surface mount integration, end plate mount integration and stator iron mount integration.

2.1 Surface mount integration

This involves the physical mounting of the power converter on the motor housing. Different variations of this concept have been proposed – from a simple mount of the PE on the case of the motor to modularising the power converter and mounting the smaller converter units on the motor housing [19–24]. In Fig. 1*a*, a simple addition of PE on the motor is shown while Fig. 1*b* shows a modularised converter mounted on the motor housing. A shared or separate cooling system could be adopted depending on application and power density requirements.

This mode of integration is particularly attractive because of its simplicity, low cost of manufacturing and relative ease of implementation [16, 23]. The housing acts as a thermal barrier providing thermal isolation between the converter and the machine (particularly the stator windings – a major heat source). The thermal management of the casing must guarantee full absorption




Fig. 2

a Danfoss VLT DriveMotor LCM 300 [26]

b Siemens SIVITEC MSA 3300 [28]

of all of the power electronic heating loss and all of the radially conducted heating loss from the machine. By redesigning the housing to accommodate an active cooling system [20], it can also act as a heat sink for the PE and converter (common thermal node) by offering a larger surface area for heat transfer and dissipation. The housing also provides mechanical stability and a mounting surface for the converter [21]. Extra thermal management and cooling mechanisms can be adopted for high power density motors where stator winding temperatures reach and sometimes exceed 200°C. Forced air cooling using fins embedded in the stator housing is employed in [20, 22] utilises a liquid cooling system by running water pipes through the stator housing.

Numerous commercially available surface mounted IMD configurations exist, with the majority focused on pumps, fans and compressor applications. Low power ratings are available, with Schneider offering the Lexium 32i range with power ratings from 0.4–2.2 kW [25]. Danfoss offer mid power range IMDs up to 7.5 kW [26] and VEM Motors [27] offers a line of IMDs (compact Line) with power ratings up to 30 kW. High power IMDs are also commercially available with the Siemens SIVETEC series for electric vehicles (EV) offering surface mount IMD systems from 30–200 kW range with power densities up to 2.6 kg/W [28]. This large range of power ratings highlights the numerous possibilities available when adopting this configuration, with limitations largely being application dependent (Fig. 2).

Recent commercially available surface mount IMDs suggest a shift from a more centralised surface mounted converter to a modular structure. Lenze offer modular low to mid-range IMDs with power ratings ranging from 0.4–7.5 kW [29]. Commercial high power modular IMDs with ratings up to 16.5 MW are currently manufactured by Siemens under the integrated drive systems range [30].

2.2 End plate mount integration

This is a variation of the surface (radial) mount configuration with converter mounting position dependent on available space in the axial direction. Like the surface mount, the end plate mount configuration provides a stable mechanical platform for the converter. It also provides thermal isolation of the PE from the machine. In the example published in literature [31], a 30 kW specialised configuration is manufactured wholly dependent on the available space for mounting and the cooling system adopted. The endplate is redesigned to accommodate the PE and any extra cooling mechanism (cooling fins) added. This design aims to protect the PE by placing them before the motor in the cooling air flow [31]. However, the machine suffers in this regard due to the redesigned end plate restricting adequate ventilation and cooling since all end winding losses must now be conducted radially. It is generally assumed that the machine robustness means it is able to

withstand elevated temperatures compared with the converter (Fig. 3).

In a very high speed machine it may be difficult to adequately ventilate the rotor if adopting this design. An extra cooling mechanism may be necessary if the IMD in question is operated at high torque and low voltage [31]. The PE position in [31] is necessary due to the available space in a predefined motor and the cooling system adopted. The PE unit was mounted on a redesigned endplate which was used as a heat sink for the power modules. Due to the lack of available space for mounting, a matrix converter was used in order to avoid the bulky energy storage elements and DC-link circuits used in traditional converter configurations [32]. The fan is redesigned (increased diameter) to compensate for the reduced air flow to the motor (Fig. 4).

Commercial endplate mounted configurations include the UQM PowerPhase HD 250 with NexDrive EV3-850 [33] and Bonfiglioli Electric PowerTrain 600D [34]. Both IMDs are for electric vehicle applications with high power ratings of 250 and 45 kW, respectively. Other manufacturers include TB Woods and ABB with a mid-range power rating portfolio between 3.7 to 7.5 kW [35, 36]. Typical applications include EV where surface integration is difficult due to lack of space in the radial direction.

2.3 Stator iron mount integration

This configuration is aimed at producing a more compact, high power density IMD. The power converter is mounted on the stator back iron as shown in Fig. 5a [6]. This concept is particularly beneficial when the height of the converter components (especially




Fig. 3 Endplate mount integration. Redesigned finned endplate with Converter Loss Simulation Resistors [31]



Fig. 4

a UQM PowerPhase HD 250 [33]

b Fig. x Bonfiglioli Electric Power train 600D [34]




Fig. 5 Back iron mount integration

a PE mounted on Stator Back Iron [6]

b Stator pole module consisting of an iron pole piece and a power converter module [11]

the DC-link capacitor) is small. The converter can fit into the space between the stator back iron and endplate.

The power converter may be segmented (modularised) around the back iron and the individual modules connected in series. The converter modules supply independent machine windings – akin to a switched reluctance machine method of energising the windings [6] or a concentrated winding. A similar design is utilised in [11] with the power converter also modularised. However, the use of silicon based PE required the need for a heat sink in every module thereby increasing the overall volume of the module. The 83 kW protean electric wheel [37, 38] is one of the very few commercially available manufactured IMD adopting this approach (Fig. 6). The benefits of having a more compact IMD due to the integration of the converter in the machine housing presents a few problems. The complexity of efficiently integrating the relatively fragile converter within the machine housing is amplified by the high vibration and shock loads the converter is subjected to in the machine enclosure [38]. The limited space within the enclosure, places the converter in close proximity to the windings. This requires careful thermal analysis to ensure the PE can withstand the localised high temperature [39]. A liquid cooling system is adopted in [38] with an axial and orthogonal path to facilitate heat transfer and improve heat dissipation – cooling both the PE and windings simultaneously Table 1.

3 Cooling systems

Close proximity integration demands power devices and modules capable of operating in harsh conditions, with elevated temperatures and thermal cycling – both active and passive. Various commercial products are unable to meet these demands and it is imperative an efficient cooling system is implemented. Cooling the integrated converter requires extensive thermal analysis of the converter and machine individually and as a unit. Adopting separate cooling systems for the converter and machine potentially increases the volume, cost and maintenance demands of the IMD.

In IMDs, the converter is mounted on or in the machine enclosure, this combines both thermal and mechanical requirements of these components into a single design problem. Combining the physical structure of both converter and machine into one housing reduces the physical size of the motor drive and reduces duplication. Adopting a unified cooling system instead of the traditional separated option tackles the thermal demands of both converter and machine simultaneously. However, since the thermal demands of the PE and machine vary (due to the large heat flux of the PE compared with the machine) a unified cooling system that efficiently accommodates both PE and machine is complicated [52]. The use of a combination of active and passive cooling




Fig. 6

a Unsprung assembly Protean in-wheel motor [37]

b Cross section of Protean in-wheel motor [38]

Table 1 Commercially available IMDs and their target applications

Company	Power rating, kW	Mounting position	Product	Application
Yaskawa	1.5–4	surface	IE4MD [40]	—
Danfoss	0.5–7.5	surface	VLT FCM 300 [26]	pumps, conveyors fans
Baldor	0.75–7.5	surface	smartMotor [41]	
Lenze	7.5	surface	8400 motec [29] [42]	fans and pumps
Grundfoss	0.75–22	surface	Grundfoss E-pump [43]	pump
VEM Group	0.5–30	surface	VEMoDRIVE compact [27]	
Rockwell Automation	1–1.4	surface	Kinetix 6000M [44]	food packaging
Leroy-Somer	5.5–7.5	surface	VARMECA 14 [45]	hoisting
Schneider	0.6–2.2	surface	Lexium 32i [25]	materials processing
Sew-Eurodrive	0.37–4	surface	MOVIMOT [46]	packaging and conveyor systems
Lenze	Up to 11 kW	surface	smart motor M300 [47]	materials processing
Siemens	30–200	surface	SIVETEC MRS/MRI [28]	EV
Ford	45–70	surface	hybrid escape [48]	EV
Alpha	Up to 0.2	endplate	ASX series [49]	—
INMOCO	0.05–0.3	endplate	pegasus integrated motion system [50]	material processing
AXOR	0.3–1.47	endplate	fast back [51]	material processing
TB Woods	0.75–3.7	endplate	E-trAC IMD [35]	—
ABB	0.75–7.5	endplate	integral motor [36]	pump and fan
UQM	140–250	endplate	Polyphase HD with NexDrive EV3-850 [33]	electric vehicles
Bonfiglioli	45	endplate	electric powertrain 600D [34]	electric vehicles
Protean	83	stator iron	Brabus E Class [37]	electric vehicle wheel

systems is inevitable in modern IMDs due to the rigorous thermal demands of the system [53].

Using an active cooling system involves forced convection cooling of the power module and machine [54, 55]. This increases the overall weight and volume of the system whilst adversely

impacting overall system performance. The substrate or base plate (heat spreader) of the converter is in direct contact with the coolant which increases the heat transfer coefficient between the converter and coolant aiding heat dissipation. The increased cost and added maintenance of the cooling system is also a drawback.

In most industrial drives and IMDs in literature, when a unified active cooling system is adopted the thermal path can be arranged in parallel or series. In a parallel path, both heat sources – the machine and PE are independent of each other. When implemented in an IMD where the heat sources are in close proximity, isolation is required. Isolation involves sectioning the power module away from heat sources in an environmentally controlled compartment but the closer the converter is to heat sources like the stator windings and iron, the harder it is to isolate [56]. This thermal path arrangement is implemented in [31, 57] with the more fragile PE is sectioned off from the machine by the redesigned end plate. Emphasis is on protecting the PE, as the machine is usually viewed as thermally ‘robust’ enough to handle elevated temperatures.


A series/unified path for the machine and converter offers a common path for heat flow. The thermal path is from the coolant to the PE then machine (or machine before PE). The varying thermal demands of both PE and machine and the large temperature gradient of the thermal path makes its implementation complicated. Most IMDs adopt either a fully parallel cooling path or a hybrid of both parallel and series cooling (Fig. 7).

In [20, 24], both converter and machine share a common thermal node for heat dissipation – the machine housing. Forced convection cooling using water pipes machined through the machine housing is incorporated. The drawback with this arrangement is the large pressure drops in the coolers and large temperature gradient that exists in the common thermal path due to the difference in thermal demands of heat sources. A series-parallel hybrid cooling system is adopted in [31], with the fan cooling the sectioned PE unit first before the rest of the machine.

In a passive cooling system, no external cooling system is utilised and heat dissipation is achieved through a combination of - natural convection, use of a thermal mass (heat sink), ventilation and thermal isolation. Thermal management using a passive cooling system can also be achieved by reducing the overall power ratings of the system, utilising high temperature operating components and increasing efficiency – in order to reduce system losses.

Converter cooling ranges from a simple heat sink or heat spreader to an advanced convection cooling system. Heat sinks and spreaders offer a cheap and simple cooling option but as the required operating temperature of the IMD increases a more efficient cooling system is required. Heat sinks and spreaders are often large compared with the cooled devices. Novel cooling concepts have been proposed for IMD for improving heat transfer [53, 58–62].

In [53, 58], Danfoss presents an improvement on the standard jet impingement cooling system by removing the coolant from the

**Fig. 7** Showing parallel and series cooling paths

a Axial View of PE mounted on Endplate – parallel path [31]

b Simplified layout of water pipes through machine housing – series path [20]




Fig. 8 Novel concept of improving heat transfer in PE module

a Temperature gradient in a standard cooling system

b Danfoss Showerpower cooling concept showing the finned baseplate and vents for coolant input and output [53]

thermal path before it starts to warm up. This eliminates the temperature inhomogeneity usually associated with a ‘series path’ cooling. A similar concept is adopted in [62] where an active cooling substrate for the PE is manufactured by machining a synthetic. In [59], a water-cooled, finned common node between the converter and machine is manufactured similar to [53]. The surface area of the common thermal path is both increased and cooled, further reducing the temperature gradient of the common sink. Infineon presents a novel parallel cooling system in [61] for EV applications. The converter module is designed to provide optimum temperature dissipation from the module and isolation from the rest of the system. A combination of active and passive cooling approaches is utilised in [61] where the power device operating temperature is reduced and the power module is redesigned to allow liquid cooling between its mounting plates. These novel concepts are aimed at improving heat transfer in PE module (Fig. 8).

A combination of forced convection (active) and passive cooling presents the only realistic cooling option for a power dense, closely integrated IMD system. This is due to the high heat transfer coefficient and low thermal resistance it offers aiding a more efficient cooling. Although low power systems will reduce thermal management demands in IMDs, close proximity integration and the shift to high power applications in recently manufactured IMDs suggests low power systems do not offer a realistic solution to the problems encountered in close proximity integration. By utilising materials that can withstand high temperatures and harsh conditions, both active and passive cooling can be utilised without compromising on power ratings.

4 High temperature devices

4.1 Wide band gap materials

With increasing demand for more efficient, higher power and higher temperature operation of power electronic converters, the challenge of increasing the efficiency and power density of converters has become more urgent for design engineers to solve [63]. Presently, silicon power devices are the dominant semiconductor choice in industry [64, 65]. However, due to basic physical restrictions, silicon power devices have reached their limits in terms of further development and scaling [66]. They also have a maximum temperature for the device junction in the range of 125–150°C [66].

Wide band gap semiconductors have been championed as the future in semiconductor technology since the 1950s [67]. High temperature and low conduction and switching losses are some of

the advantages of wide band gap semiconductors in power devices [68]. Their ability to operate at higher power densities, voltages and frequencies are also potential advantages that make them beneficial in power device applications.

Table 2 shows the material properties of the most common wide band gap semiconductors compared with silicon. The wide band gap semiconductor devices exhibit superior physical properties compared with silicon devices [70–74]. Diamond potentially exhibits much better properties compared with silicon carbide (SiC) or gallium nitride (GaN). However, there has been a lack of development due to financial cost of implementation, material availability and its low coefficient of thermal expansion (CTE) [75]. There are also significant manufacturing issues due to a lack of efficient methods to create conventional devices that rely on doped layers.

For packaging, it is essential that the CTE of the semiconductor material matches the electrically insulating ceramic board [76]. This allows the semiconductor material to be easily adapted for higher temperature applications. GaN and SiC are a technically and commercially realistic competitor for Si in the power semiconductor market compared with diamond and are becoming widely available [77–81].

4.2 Silicon carbide against gallium nitride

SiC and GaN are two important wide band gap materials for future switching and RF power applications. SiC and GaN both exhibit higher thermal conductivity and bandgap energy compared with Si [82]. With GaN’s higher electron mobility compared with SiC and Si, GaN should ultimately be the best device to provide lower losses at higher frequencies [83]. High frequency operation allows

Table 2 Material properties of Si, SiC, GaN and Diamond [69]

Property	Si	6H-SiC	4H-SiC	GaN	Diamond
bandgap E_g (eV)	1.1	3.03	3.26	3.45	5.45
dielectric constant, ϵ_r	11.9	9.66	10.1	9	5.5
breakdown field, E_c (kV/cm)	300	2500	2200	2000	10,000
electron mobility, μ_n (cm ² /Vs)	1500	500	1000	2000	2200
hole mobility μ_p (cm ² /Vs)	600	101	115	850	850
thermal conductivity, λ (W/cmK)	1.5	4.9	4.9	1.3	22
thermal expansion ($\times 10^{-6}$)/°K	2.6	3.8	4.2	5.6	1–2
saturated E-drift velocity, V_{sat} ($\times 10^7$ cm/s)	1	2	2	2.2	2.7

for smaller parasitics, especially DC–DC capacitors. This leads to a reduction in the overall volume and increase in power density of an IMD incorporating GaN power devices.

The energy band gap of SiC is lower than GaN. Since a larger band gap results in a smaller generation of carriers in the depletion regions of devices, it is favourable for reducing the leakage current of devices which utilise P-N junctions to support voltages. The larger band gap is also favourable for producing metal-semiconductor contacts with larger Schottky barrier heights. This means GaN in theory can produce thinner devices for a rated voltage compared with SiC [84]. For a given voltage rating both GaN and SiC will produce smaller devices compared with Si, making them highly beneficial for IMDs due to the limited space available for integration.

In power devices, the breakdown electric field strength determines how high the largest field in the material is before breakdown occurs. This allows SiC and GaN to operate at much higher voltages and lower leakage currents compared with Si. With SiC and GaN exhibiting significantly higher values compared with Si, higher power rated devices can be produced. This is particularly beneficial in IMDs where power density is important. SiC and GaN can produce smaller devices with higher power ratings compared with Si.

The maximum operational temperature of a semiconductor material is determined by the bandgap. The temperature limit is reached when the number of intrinsic carriers approaches the number of purposely added (extrinsic) carriers. Therefore, semiconductors with wider bandgaps can operate at higher temperatures. In IMDs that demand operating temperatures higher than 150°C, SiC and GaN provide a realistic integration option since they can produce devices with a practical temperature limit of 600°C compared with Si with a temperature limit of 225°C [57].

The thermal conductivity of the material determines how quickly and efficiently it conducts heat to its surroundings [85], however, packaging limits restrict the overall maximum operating temperature. SiC has a higher thermal conductivity compared with GaN and hence SiC can theoretically operate at higher power densities compared with GaN devices. Efficient heat dissipation is important in IMDs, especially the converter unit due to the high heat flux it produces over a small area (compared with the machine). By utilising SiC PE devices, the converter module temperature can be reduced further decreasing the overall IMD temperature.

Manufacturers argue that both devices do not overlap in competition but have distinct benefits for specific applications. GaN is thought to be the obvious choice for low voltage applications (<600 V) and SiC better for high voltage applications (>1000 V) [86]. However, between 600 and 1000 V the choice between SiC and GaN is application dependent.

SiC poses significant advantages over GaN in power device application due to a number of reasons. Some of them include [87–91]

- The lack of native oxide in GaN restricts production of GaN MOS devices. However, SiC uses SiO₂ as a native oxide.
- GaN as a material possesses a lower thermal conductivity (about one-fourth) compared with SiC. For high power, high temperature operation applications, this is particularly important as heat needs to be dissipated quickly and efficiently.
- The cost of manufacturing pure GaN wafers due to the difficulty in growing GaN boules is higher than that of SiC. GaN wafers are usually grown on SiC or Sapphire. However, recently, GaN wafers are grown on Si producing potentially cheaper devices compared with SiC [88]. The epitaxial growth of GaN on the silicon wafer is the sole cost disadvantage.

5 Modular integration

Modular integration involves segmenting the PE into smaller modules that control dedicated stator winding sections. These modules are physically independent of each other and are usually

connected together in series or parallel for the purpose of control. An active voltage (or current if connected in parallel) balancer is usually required to balance and regulate the segment voltages during unbalanced or asymmetrical load conditions. Advantages of modular systems include fault tolerance, better thermal capabilities, power rating scalability and a possible reduction in the overall size and cost of the PE.

Drive modularisation is independent of converter position as mounting can occur on the motor housing [22] on the stator iron [6, 10] or on the end plate [31]. Fault tolerance is one obvious advantage as multiple modules exist which form a unit as opposed to a centralised PE module. The system can be designed to allow for individual module failure. Current and voltage loading stress is also reduced in the PE as lower rated components are used in the modules to form a much larger rated unit [92].

The size of the components can also be reduced as the ratings for independent modules and their passive component sizes are a lot lower compared with a central PE unit.

Improved thermal capability is another possible advantage. This is as a result of having individual lower rated components and more evenly distributed heat dissipation [93].

Due to these potential benefits, modular drives are very beneficial for IMD design. In [6], both machine and drive are modularised (one converter phase leg per machine pole) and the benefits include – better thermal performance due to lower rated devices, increase in machine lifespan as a result of low voltage change in the slot insulation layer, lower maintenance cost and fault tolerance. A similar concept termed ‘site of action integration’ is applied in [13] for EV integration with resulting benefits of shorter connecting wires. The possible drawbacks are the necessity for a complex control system for the individual power modules and the difficulty of mechanically and structurally integrating the modules with the motor [94].

6 Converter topologies for IMD

Power electronic converter configurations and topologies have been analysed extensively in [95]. The topologies analysed include;

- Three phase buck converter
- Vienna rectifier
- Discontinuous conduction-mode boost converter
- Continuous conduction-mode boost converter
- Matrix converter
- Two-stage direct power converter with reverse blocking-IGBTs in the rectification stage

As the results of converter topology comparison are application-dependant, it is not possible to determine a single best topology for any IMD. The pros and cons of each topology are investigated below, focusing mainly on aspects more related to possible integration.

6.1 Matrix converter

The matrix converter is a forced commutated direct ac–ac converter that uses an array of nine controlled bidirectional switches as the main power elements to create a variable output voltage system with unrestricted frequency [32]. The conceptual scheme of a matrix converter is depicted in Fig. 9.

The potential advantages of this topology include a relatively compact size (no need for dc-link capacitors), sinusoidal input current, bi-directional power flow (power regeneration capability) and a controllable input power factor [32]. It is an attractive prospect in applications where volume, reliability and weight are important – particularly in IMDs.

Its main disadvantages are a low voltage transfer ratio of 0.86, the necessity of an additional clamping circuit for protection and of a mainly capacitive input filter. Moreover, it suffers from high cost due to the large amount of switching devices (18 IGBTs and 18




Fig. 9 Matrix converter

diodes) and due to the non-conventional arrangement requiring custom made power modules. The absence of a dc-link capacitor means no decoupling between the input and output, and also the complete absence of ride-through capabilities [96].

6.2 Two-level full bridge converter

The two-level full bridge topology is the workhorse of PE as we know it. It is a very well-known structure (Fig. 10), relatively simple to drive and flexibly controllable with different algorithms to suit the application. It can be used in both inverter and rectifier mode (bidirectional power flow). Being so common, power modules with this arrangement are easily available on the market, with power ratings ranging from a few hundred Watts to MWs, and both based on Si (MOSFETs and IGBTs) and SiC technologies (MOSFETs and JFETs), thus a custom designed power module is not required.

A drawback of this topology when compared with multi-level topologies (as will be described below) is the relatively higher current THD, even when operated in PWM. The level of the THD and its impact is electrical machine dependent and hence this needs assessing for any given machine.




Fig. 10 2-level full bridge converter

6.3 Three-level neutral point clamped (NPC) converter

The three-level NPC topology is probably the most known of the three-level AC/DC converter topologies and it is gaining strong industrial acceptance. The main benefit of using a multilevel converter structure is the reduced current THD which can be achieved when compared with conventional two-level structure operated at the same switching frequencies. This will naturally lead to higher achievable fundamental frequencies making this configuration desirable for high speed applications. Additional benefits in terms of conversion efficiency gains may occur if the converter is designed such that lower voltage rating devices are used, which in turn would lead to reduced switching losses. A reduction in the current THD is also closely related to a reduction in machine losses, and can potentially ease the IMD overall thermal management.




Fig. 11 3-level NPC full bridge converter

The main drawbacks of this arrangement is the necessity to balance the DC-link midpoint (using relatively complex control algorithms) and the high number of active devices, resulting in a lower reliability, added complexity and an increased cost. As this topology is gaining popularity for a range of energy conversion applications including automotive and industrial, there is a reasonable selection of commercially available power modules for this topology. The structure of the three-level NPC full bridge is depicted in Fig. 11.

6.4 Multiphase full bridge converter

Multiphase full bridge topology (Fig. 12) is derived from the conventional full bridge arrangement. With respect to this it presents a potentially more complex control algorithm (depending on machine windings arrangement and number), however it also presents a number of advantages such as increased fault tolerance as well as increased power processing partitioning (feature highly desirable in an IMD). As full bridge converters, multiphase full bridges can be used in both inverter and rectifier mode (bidirectional power flow) and suffers from the same drawbacks. The same considerations can be made for PE modules and technologies.

The number of phases in electrical drives is typically three, driven partly by convention and partly by a compromise between number of devices and machine utilisation. Three phases represents the best compromise between the two in most conventional scenarios. The following are some considerations whilst selecting the number of phases:




Fig. 12 Multiphase full bridge converter

- Single phase: this represents a very cheap converter solution however the machine is typically characterised by very high torque ripple, vibration and losses. This is due to the inability of establishing a rotating field in the machine.
- Two phase: a two phase drive can be fully functional and effective when compared with three and higher phase number alternatives as in all cases a rotating field can be established. It can be a suitable solution for high speed drives especially for cost-sensitive applications without high torque requirements. The downside of such a drive is the typically lower torque density of the machine and higher torque ripple.
- Four-phase and higher: will present a solution with an improved torque density and lower torque ripple when compared with three phase machine drives. However this comes at the extra cost of having more components. Higher phase numbers are however attractive when high power drives are to be connected to low

voltage networks such in automotive applications. Channelling the power through more phases limits the current requirements of devices and thus their size, allowing for an easier structural integration into the machine, as well for more spatially distributed PE-related losses.

7 Passive components

Passive components (especially capacitors) account for a considerable amount of the material cost and volume of a power electronic system. Fig. 13 gives a graphical illustration of the material costs and volume of passive components compared with other components in a PE system. At high temperatures capacitors are particularly challenging due to thermal limits of many common capacitor materials. Leakage currents also occur at high temperatures making it hard for the capacitor to hold charge [57].

The DC link capacitor helps avoid over-voltage during commutation and provides a low impedance path for the switching harmonics, effectively buffering the ripple current, but passive DC-link capacitors are often bulky and expensive.

There are four main capacitor technologies available

- Multi-layer ceramic capacitors
- Electrolytic capacitors
- Film capacitors
- Electro-chemical double layer (ECDL)




Fig. 13 Typical material cost and volume distribution in power electronics system [13]

7.1 Ceramic capacitors

The MLCC is the most dominant form of ceramic capacitor. Its most important attributes are its high capacitance and compactness [97–99]. The most expensive of the four capacitor options, ceramic capacitors offer very high AC current ratings, high temperature operation (up to 200°C) and small size. It is also the most widely used passive component in modern electronics [100] and has high energy density.

Ceramic capacitors are not limited to MLCCs. Bespoke capacitors exist with unique capabilities lacking in other capacitor technologies [100]. High temperature ceramic capacitors that can withstand temperatures of up to 250°C exist [101]. Ceramic capacitors are used mostly for high temperature and high voltage applications [102]. The major disadvantages are the high cost and the brittle nature of ceramic capacitors [103, 104]. In IMD traction applications where shock and vibration is prominent, reliability issues arise over the mechanical stability of ceramic capacitors. Moreover, the low energy density of ceramic capacitors mean several components have to be paralleled up to achieve the necessary ratings required. This further increases the overall cost of the IMD system.

7.2 Electrolytic capacitors

These capacitors are mostly used in the rectification stage of switched mode power supplies [105]. The cheapest and most popular of the four options, electrolytic capacitors achieve the highest storage densities (up to 1 J/cm³) but have the lowest AC current ratings. Operating temperature is usually up to 120°C [106]. Although electrolytic capacitors are the standard choice for dc link storage in conventional motor drives, their limited current handling capabilities and operating temperature restricts their use in integrated drives. In addition, due to their physical construction, they show a relatively high equivalent series resistance and equivalent series inductance, thus posing a limit at the converter maximum switching frequency of operation. The thermal limitation is a problem especially in IMDs due to the compact nature of the unit.

Theoretically the maximum voltage for electrolytic capacitors is 800 V. However, practically the maximum voltage is 600 V [107]. This makes electrolytic capacitors susceptible to voltage surges. Electrolytic capacitors are also polarity dependent thus restricting their applications to DC circuits.

Thermal degradation of the electrolytic capacitor is a heat triggered electrochemical reaction [108, 109]. Thermal degradation causes a relatively short life time of electrolytic capacitors compared with ceramic and film capacitors [110]. Although electrolytic capacitors have very high energy densities, In IMD integration, their bulky size and short life time due to thermal degradation means they hardly feature as passive components. This is due to the high operating temperatures and limited integration space in the IMD enclosure.

7.3 Film capacitors

Polymer film capacitors are the most flexible in device geometry of the aforementioned capacitor technologies. They combine the advantages of low losses and mechanical robustness with high volume capacitance. They are also polarity independent providing true bipolar operation. Typical applications include high frequency inverters and solid state switch snubbers. They are also capable of operating at higher voltages (up to 100 kV) [111]. Their ability to work under high electric field coupled with their high energy density is an advantage [112, 113]. Theoretical operating temperatures can reach up to 220°C, however, commercially available film capacitors operate at temperatures up to 170°C [114]. They also exhibit higher life time and higher ripple current capability compared with electrolytic capacitors [115].

Their main disadvantages include their high cost, lower capacitance per volume compared with electrolytic capacitors and low-medium operating temperatures. Despite these disadvantages, film capacitors offer a realistic capacitor choice in IMDs due to its small size and longer life time compared with electrolytic capacitors and its mechanical robustness and high energy storage density compared with ceramic capacitors.

7.4 Electro chemical double layer

Chemical double layer capacitors also known as ‘supercapacitors’ are low energy (compared with electrochemical batteries), high power density storage devices [116]. Although not as prominent as the aforementioned types of capacitors, they have been commercially available for decades [117]. Typical applications include backup and recovery systems and as energy storage for EV [118].

The relatively high cost [119] and high self-discharging rate [120] are potential drawbacks of the ECDL. Its low operating temperatures compared with other types of capacitor also makes ECDL capacitors unlikely to see successful application in IMD. They also have a very low operating voltage per cell which means that large numbers of cells connected in series are required as well as complex balancing circuits to ensure that the cell voltages remain equalised throughout the stack [121].

8 Packaging of power electronics module

In an IMD, the converter is arguably the most sensitive component in the system. The growing demand for an efficient, high temperature operable converter has led to advancement in research on wide band gap devices [122]. High temperature environments like combustion engines in aircraft and automobiles could benefit from a high temperature integrated power module. The ability for a power module to operate at a high temperature results in a smaller system size of the IMD and reduced costs of the cooling system.

Wide band gap devices like SiC and GaN can theoretically operate at temperatures above 500°C while Si is restricted to junction temperatures lower than 175°C [123–125]. Above 200°C Si devices experience latch-up at reverse bias junctions and leakages [57]. SiC power devices exist with operating temperatures up to 200°C [126–129], but the maximum temperature of a SiC power module for example is limited to about 150°C [130, 131]. A commercial high temperature SiC module has been reported operating at 250°C [132]; however, reservations exist over its reliability above 200°C.

The packaging of the PE module primarily restricts its maximum operating temperature [133, 134]. The module undergoes high thermal and thermo-mechanical stresses at high temperatures leading to critical failures in the system [135, 136]. Degradation of polymeric materials used in the module packaging as well as the creation of intermetallic compounds, which may weaken the joints also occur at high temperatures [124, 137, 138]. Categories of interest in power module packaging are – interconnects, die attachment, substrate choice and encapsulation [139].

8.1 Interconnects

Conventional power modules use aluminium, copper or gold wire bonds as the main current path for interconnection [140, 141] and the wire bond is arguably the weakest part of the power module [142, 143].

At temperatures above 200°C, the reliability and mechanical stability of aluminium bonds is drastically reduced [87, 142] with wire bond lift-off or wire bond breakages the most common failures [144]. These failures usually occur at the heel of the wire bond – where the most stress occurs [145, 146]. The thermal resistance of the wire bonds also increase at high currents and temperatures [61, 147].

Alternative interconnect options that offer high temperature operation and reliability over 200°C will improve the life time of PE modules in IMDs. Large diameter platinum wires have been investigated for high temperature application integration. Despite exhibiting exceptional mechanical strength at high temperatures, CTE mismatch with the semiconductor and low electric conductivity are some of its disadvantages [148]. Silver alloy wire bonds have also been investigated for high temperature operation [149]. Its high thermal conductivity is also beneficial in IMD applications [150]. Flip chip technology can also potentially replace standard interconnections by connecting the power devices directly to the package through conductive metallic bumps [151]. In [152], a highly power dense, wireless converter module for IMD integration is presented using flip chip on flex (FCOC) technology with improved thermal performance.

8.2 Die attachment

The die attachment is the connecting interface between the substrate and the die ensuring that the die is mechanically stable on the substrate and thermally efficient in heat transfer to the substrate [153].

Materials used for die attachment ranges from high lead and lead free solders to silver sintered layers [154–158]. Solders are the most common die attachment but often have a low working temperature. However, Sn based solder alloys have been reported to possess working temperatures more than 280°C [159–161]. However, its low thermal conductivity restricts efficient heat transfer in power

modules. Zinc alloy solders have also been reported to operate at temperatures above 200°C [162].

Sintering offers the best die attachment option boasting working temperatures up to 650°C and thermal conductivity orders of magnitude higher than solder [163–167], properties particularly beneficial for IMD integration. However, a very high pressure (around 30 MPa) is required to achieve sintering leading to potential cracks or possible destruction of the relatively fragile ceramic substrate. Silver particle pressure-less bonding has been reported in literature and provides an alternative for silver sintering without the substrate subjected to high pressures [168].

8.3 Encapsulant

The encapsulant acts as a protective barrier for the power chip and components from hostile environments. It also acts as a heat spreader and can prevent arcing at high voltages [169, 170]. In close proximity drive integration (like back iron mount integration), the PE encapsulant will be subjected to high ambient and operating temperatures. It is therefore important the chosen encapsulant can withstand such high temperatures and harsh environment. Typical encapsulation materials are silicone gel, epoxy and parylene with the later showing high working temperatures more than 200°C. Several encapsulants claim to have working temperatures more than 250°C [171–181]; however, reliability studies claim encapsulants slowly degrade before reaching 250°C [137, 182].

8.4 Substrate

The substrate provides electrical isolation, mechanical support and thermal conductivity for the circuitry of the power module. It consists of a thin ceramic substrate sandwiched between two layers of copper or aluminium metallisation. Popular ceramic materials are – alumina, aluminium nitride, silicon nitride and Beryllia. Alumina is the cheapest and most common option but has the lowest thermal conductivity compared with others [183, 184]. Aluminium nitride (AlN) possesses a higher thermal conductivity and its CTE matches SiC [185, 186]. However, its mechanical strength is poor [187]. Beryllia although exhibiting an excellent thermal conductivity is a toxic material raising health and environmental issues. Silicon nitride (Si₃N₄) is fairly new hence its limited supply. It has average thermal and electrical characteristics but excellent mechanical properties.

In IMD integration, high mechanical strength, high thermal conductivity and a close CTE to the power devices utilised are some of the properties required. The choice between Si₃N₄ and AlN is application dependent with AlN used for a power dense IMD where efficient heat dissipation is paramount. In applications with high vibration levels (close proximity integration applications), Si₃N₄ is a better option for IMD integration with fracture toughness levels twice AlN's [140].

Other packaging technologies have been investigated in search of a more compact high temperature operation. Flip chip technologies present a compact wireless configuration [188–191] but reservations exist over its mechanical stability and mechanical stress at high temperatures [143, 192]. FCOC substrates [193] have also been reported to reduce stress between solder joints, devices and substrates. Flex substrates also provide the flexibility of producing power modules with distinct shapes especially beneficial in IMD integration due to the lack of available mounting space [194]. Another wireless packaging technique – a variant of FCOC, utilising a 'SKIN' flex layer is presented in [195] promising improved thermal capabilities and power density compared with a standard power converter. Pressure contact technology has also been investigated as a possible replacement for aluminium wire bonds for high temperature applications [196, 197]. Its high manufacturing costs and complicated manufacturing process remain drawbacks in manufacturing. Careful selection of materials in the module is also important to avoid CTE mismatch. CTE mismatch can lead to die fracture, fatigue and lifting, horizontal

crack propagation, delamination and cracking of the ceramic substrate [57, 198, 199].

The thermal and mechanical properties of a standard PE module components will limit its successful integration in a machine. Manufacturing a specialised power module by utilising WBG devices like SiC and GaN with high temperature operating die attaches, encapsulants and interconnects will aid successful close proximity integration. Moreover, adopting specialised packaging techniques like FCOC and 'slot-module' [94] can improve power density and heat dissipation in the power module.

9 Challenges in IMD design

The emphasis on smaller, more efficient and power dense converters has led to rapid development in converter technologies. Devices able to switch at higher frequencies allow for a reduction in size of power devices like magnetics and capacitors. Compared with the machine, the converter has a much higher power density with typical heat flux densities in the range of 50–500 W/cm² for power semiconductor devices, compared with 0.1–3 W/cm² for magnetic components and less than 0.1 W/cm² for capacitors [200]. This is due to its smaller volume and high power handling capabilities [201].

The converter losses are concentrated over a smaller area leading to localised high temperatures (hot spots). This leads to complications in converter cooling and thermal management especially in close proximity to other heat sources such as stator windings [202]. Losses in the machine frame also increase the overall temperature of the IMD system. This limits the power dissipated by the converter, consequently decreasing its power handling capabilities [203].

Poor thermal contact between the converter baseplate or substrate and the mounting position could potentially be problematic depending on the quality of both surfaces [20, 24]. A poor thermal contact between both surfaces will increase the thermal resistance and cause poor heat transfer between the converter and machine. This is particularly troublesome when a singular cooling system is adopted in the IMD as the housing area is used as a heat sink for the converter and efficient heat transfer between the machine and PE is important.

The complexity and cost of installing a cooling system to efficiently dissipate heat from the converter and machine is also challenging.

Vibration and mechanical stability also pose reliability issues in drive integration. Machines that operate in hostile environments such as traction applications are exposed to high shock and vibration levels. Mounting the converter on or in the housing of these machines exposes the converter to significant vibration problems [6, 22]. Reliability of attachment methods such as thermal-joint compounds and screws may be severely affected by high vibration levels [22].

To tackle the pressing thermal and mechanical issues encountered in IMD design, future research in the following options should be considered

- Advancements and efficient implementation of an active cooling system
- Manufacture of bespoke modularised converters
- Utilising high temperature devices

Future research into these topics will help adapt the cooling system, converter and machine components to the rigorous thermal and mechanical demands of an IMD system.

10 Future trends

Major challenges associated with PE integration include limited available installation space, high thermal and mechanical stresses on devices and machine components and the complex cooling systems needed. Current IMDs are as a result of a pre-defined

converter installation space on or around the machine housing, usually as a result of the mechanical requirements of the machine, with little to no consideration on the converter needs. Increasing the power density, reliability and efficiency of IMDs whilst reducing the overall manufacturing cost has led to active research and development of smaller, more efficient power modules.

By exploiting the benefits of wide band gap devices, manufacturers have been able to produce devices that can withstand the rigorous thermal, mechanical and electrical demands of close coupling integration. GaN and SiC are expected to phase out Si as choice semiconductors in IMD applications. Compared with GaN, SiC has a distinct time and technology advantage in discreet power devices and module commercialisation and is expected to feature in future IMDs as the choice converter module or power device. 'Full' SiC power modules already exist providing high efficiency, temperature operation and power density whilst maintaining a small volume for machine integration. However, with GaN's ability to operate at higher frequencies compared with SiC and ongoing research in cheaper alternatives on growing GaN boules, GaN is expected to compete fiercely in power device manufacturing with SiC. Diamond although exhibiting superior properties compared with SiC or GaN is still decades away from commercialisation and is not expected to feature in PE modules in the near future.

Advancements in passives technology has also led to smaller high temperature operation devices with ceramic capacitors exhibiting operating temperature greater than 200°C. It is expected that the compactness, high capacitance and thermal capabilities of the ceramic and film capacitors will see them feature heavily in IMD converter modules in future. Aluminium nitride is expected to remain the choice ceramic for power modules, however, research into silicon nitride (Si₃N₄) which possesses better mechanical properties should provide competition for AlN in the next few years. Currently, the copper layer on the ceramic substrate is usually nickel and/or gold plated in other to avoid oxidation of the copper layer. However, at very high temperatures (above 400°C) breakdown of this oxidation layer occurs – compromising reliability [187]. Extensive ongoing research into alternate finish materials like titanium, lead and molybdenum could offer realistic alternatives to gold and nickel finishes.

These advancements in material and packaging technologies have led to more production of commercial high power IMDs. This suggest the 7.5 kW limit previously recognised as the threshold practical power rating of commercial IMDs has increased and will continue to do so. A shift from low/mid power rated IMDs to high power rated IMDs is also expected as WBG devices, improved component materials and better packaging techniques are properly incorporated in power modules and IMDs. Moreover, recently manufactured IMDs suggest a shift from the popular surface mount configuration to a more close proximity integration with the converter integrated in the machine housing. Bespoke modular converter units enable close proximity integration and will see an increase in more power dense IMDs manufactured.

Typical IMD applications include pump and fans, however, high power rated IMDs capable of high temperature operation currently feature heavily in EV and HEV application. It is expected that IMDs will continue to feature in electric vehicular systems especially 'under-the-hood' and motor tire environments where limited space and high operating temperatures exist.

11 Conclusions

In this paper, existing IMD technologies are presented. IMDs offer a more efficient, power dense option compared with a conventional machine and converter. The mounting position of the converter is wholly dependent on the available space in the machine housing, the target application and the cooling system adopted.

Wide band gap devices like SiC and GaN provide a realistic option for IMDs by offering a more compact and efficient converter capable of high temperature operation. However, the packaging of these power modules hinders exploiting their full potential.

Modularisation of the converter into smaller units will also help reduce the thermal stress on the devices and efficiently utilise available space around the machine housing. It will also help adapt the converter into the small confines of the machine housing.

Forced convection cooling and advanced packaging techniques allow the converter efficiently dissipate heat. This potentially allows close integration of the converter with the machine and a singular cooling system for the IMD.

Development of converter technologies, more efficient and robust passive components (especially capacitors), increased reliability, better packaging and semiconductor materials such as SiC and GaN will enable PE to meet the harsh and rigorous environmental conditions the converter faces in an IMD.

IMD design should involve a holistic analysis of the thermal, mechanical and electrical effects of the IMD components and the cooling system as a single unit. Manufacture of more mid and high power rated IMDs is expected with advancements in material and packaging techniques. Industrial applications like EVs and HEVs and material processing will benefit from high power density IMDs.

Co-manufacturing issues may arise over the production of IMDs since the manufacture of converters and machines are often very different. Machines manufacturers may view IMD design from a machines' perspective and vice versa for converter manufacturers. This raises the question of who designs an efficient IMD – PE or machines manufacturers? Since in reality both machine and PE modules are produced by different manufacturers, creating highly adaptable modular PE units and machine will aid IMD production. It is imperative both machine and converter are designed around the requirements each component has both individually and as part of a system.

12 References

- Bartos, F.J.: 'Combination motors and drives move to make their mark' Control Engineering Online, December 2000. Available at <http://www.csemag.com/single-article/combination-motors-and-drives-move-to-make-their-mark/d9a8ab08897749f02e39653e06a6cc49.html>
- Bartos, F.J.: 'Integrated motor-drives seek wider market, user acceptance', *Control Eng.*, 2000, **47**, (13), pp. 19–23
- Viorel, I.A., Szabo, L., Ciorba, R.C.: 'Integrated motor and control unit for industrial variable speed drive'. Available at <http://citeseerx.ist.psu.edu/viewdoc/download?doi=10.1.1.301.2182&rep=rep1&type=pdf> accessed November 2015
- Hornberger, J.M., Cilio, E., Schupbach, R.M., *et al.*: 'A high-temperature multichip power module (MCPM) inverter utilizing silicon carbide (SiC) and silicon on insulator (SoI) electronics'. Power Electronics Specialists Conf. PESC, 2006, pp. 1–7
- Babb, M., Bartos, F.: 'Integrated motor drive combinations', *Control Eng. Eur.*, 2001, **57**, (21), p. 66
- Wang, J., Li, Y., Han, Y.: 'Evaluation and design for an integrated modular motor drive (IMMD) with GaN devices'. Energy Conversion Congress and Exposition (ECCE), IET, 2013, pp. 4318–4325
- Agarwal, S.H., Ryu, S.H., Krishnaswami, S., *et al.*: 'a review of high power, high temperature SiC devices'. High Temperature Electronics Conf. HITEC 2006, May 2006
- Williamson, S., Jackson, D.C.: 'Integrated drives for industrial applications'. Proc. of PCIM'99, Intelligent Motion, 1999, pp. 9–13
- Thoegersen, P., Blaabjerg, F.: 'Adjustable speed drives in the next decade. The next step in industry and academia'. Proc. of PCIM '00, Intelligent Motion, pp. 95–104
- Vas, P., Dury, W.: 'Electrical machines and drives: present and future'. Proc. of Electrotechnical Conf. (MELECON '96), vol. 1, pp. 67–74
- Brown, N.R., Jahns, T.M., Lorenz, R.D.: 'Development of a converter for an integrated modular motor drive'. Centre for Power Electronics Systems (CPES) 2007. CPES, pp. 419–425
- Nie, Z., Emadi, A.: 'Integrated converters for switched reluctance motor drives'. Power Electronics and Motion Control Conf., 2004. IPEMC, 2004, vol. 2, pp. 487–490
- Marz, M., Schletz, A., Eckardt, B., *et al.*: 'Power electronics system integration for electric and hybrid vehicles'. 2010 Sixth Int. Conf. IEEE Integrated Power Electronics Systems (CIPS), pp. 1–10
- Mohammed, O.A., Liu, S., Liu, Z.: 'Physical modelling of pm synchronous motors for integrated coupling with machine drives', *IEEE Trans. Magn.*, IEEE, 2005, **41**, (5), pp. 1628–1631
- Zeng, L., Chen, X., Nong, X., *et al.*: 'FE-based physical model of LPMBDCM for integrated motor drive system analysis'. Third Int. Conf. IEEE Innovative Computing Information and Control, ICICIC '08. 2008, p. 581
- Klumppner, C., Nielsen, P., Boldea, I., *et al.*: 'A new matrix converter motor (MCM) for industry applications', *IEEE Trans. Ind. Electron.*, 2002, **49**, pp. 325–335
- Hagbhin, S., Khan, K., Zhao, S., *et al.*: 'An integrated 20-kW motor drive and isolated battery charger for plug-in vehicles', *IEEE Trans. Power Electron.*, 2013, **28**, (8), pp. 4013–4029
- Hagbhin, S., Thiringer, T., Carlson, O.: 'An integrated split-phase dual-inverter permanent magnet motor drive and battery charger for grid-connected electric or hybrid vehicles'. 20th Int. Conf. on Electrical Machines (ICEM). IEEE., 2012, pp. 1941–1947
- Pickering, S., Thovex, F., Wheeler, P., *et al.*: 'Thermal design of an integrated motor drive'. IECON 2006–32nd Annual Conf. on Industrial Electronics IEEE, pp. 4794–4799
- Tenconi, A., Profumo, F., Bauer, S.E., *et al.*: 'Temperatures evaluation in an integrated motor drive for traction applications', *IEEE Trans. Ind. Electron.*, 2008, **55**, (10), pp. 3619–3626
- Wolmarans, J.J., Gerber, M.B., Polinder, H., *et al.*: 'A 50 kW integrated fault tolerant permanent magnet machine and motor drive'. IEEE Power Electronics Specialists Conf., 2008, pp. 345–351
- Biswas, P.S., Das, N., Biswas, S.K.: 'Design consideration of an integrated induction motor drive to replace auxiliary dc motors in locomotives'. Int. Conf. on Power Electronics and Drives Systems IEEE. 2005, vol. 2, pp. 872–875
- Shakweh, Y., Owen, G.H., Hall, D.J., *et al.*: 'Plug and play integrated motor drives'. Proc. of IEE Power Electronics, Machines and Drives Conf. (PEMD'02), 2002, pp. 655–661
- Farina, F., Rossi, D., Tenconi, A., *et al.*: 'Thermal design of integrated motor drives for traction applications', *Power Electron. Eur. Appl.*, 2005, p. 10
- 'Schneider Lexium 32i'. Available at http://download.schneider-electric.com/files?p_Reference=0198441113956-EN&p_EnDocType=User%20guide&p_File_Id=681840597&p_File_Name=LXM32iECT_Manual_V100_EN.pdf, accessed November 2015.
- 'Danfoss VLT DriveMotor FCM 300'. Available at http://www.danfoss.com/NR/rdonlyres/40FA1C95-CFB6-4BA1-A69D-D36F61436B59/0/FCM300_FactSheet_PF009A02.pdf, accessed November 2015
- 'VEMoDRIVE – variable speed drives'. Available at http://www.vem-group.com/fileadmin/content/pdf/Download/Brosch%3BCren/Flyer_VEM-motors/28_PB_en.pdf, accessed November 2015
- 'Innovative motor technology for hybrid and electric vehicles'. Available at http://w3.siemens.com/topics/global/de/elektromobilitaet/PublishingImages/antriebe-pkw/pdf/sivetec-mrs-mri-siemens_en.pdf, accessed November 2015
- 'Lenze Inverter Drives 8400 motec'. Available at <http://www.actechdrives.com/PDF/Lenze/Lenze-8400-Motec-Inverters.pdf>, accessed November 2015
- 'Siemens Multiple Drive for Vertical Mills'. Available at <http://www.industry.siemens.com/drives/global/en/gear-units/application-specific-gear-units/vertical-mills/flender-multiple-drive/pages/default.aspx>, accessed November 2015
- Wheeler, P.W., Clare, J.C., Apap, M., *et al.*: 'An integrated 30 kW matrix converter based induction motor drive'. PESC '05. IEEE 36th Power Electronics Specialists Conf., IEEE., 2005, pp. 2390–2395
- Wheeler, P.W., Rodriguez, J., Clare, J.C., *et al.*: 'Matrix converters: a technology review', *IEEE Ind. Electron.*, 2002, **49**, (2), pp. 276–288
- 'UQM and Kinetics present integrated motor and multi-speed transmission for commercial Evs'. Available at <https://chargedevs.com/newswire/uqm-and-kinetics-present-integrated-motor-and-multi-speed-transmission-for-commercial-evs/>, accessed November 2015
- 'Bonfiglioli 600D - Electric powertrains for lightweight vehicles'. Available at <http://www.bonfiglioli.co.uk/en-gb/mobile/products/electric-solutions/powertrains/product/600d-electric-powertrain/>, accessed November 2015
- 'E-Trac IMD integrated motor drive'. Available at http://www.southernpower.com/pdf/woods/electronic_products_guide.pdf, accessed November 2015
- Henze, M.: 'The Integral Motor – a new variable-speed motor drive'. Available at <http://library.e.abb.com/public/82be3ed09497afb3c1256dd00346fb6/04-08m181.pdf>, accessed November 2015
- Fraser, A.: 'IN-WHEEL ELECTRIC MOTORS - The packaging and integration challenges'. Available at http://www.proteanelectric.com/wp-content/uploads/2013/07/In_Wheel_Electric_Motors_AFraser_ProteanV4.pdf accessed 12 April 2015
- Perovic, D.: 'Making the impossible, possible – overcoming the design challenges of in wheel motors', *EVS26 Int. Battery, Hybrid and Fuel Cell Electric Vehicle Symp.*, 2012, **5**, pp. 514–519
- Mueller, S.I., Nellis, G.F., Jahns, T.M.: 'Model and design of an aircooled thermal management system for an integrated motor-controller'. Proc. of 2005 CPES Power Electronics Seminar, pp. 145–152
- 'Integrated IE4 motor-drive is 'up to 40% smaller' Yaskawa 4 kW. Available at <http://en.ofweek.com/new-products/Integrated-IE4-motor-drive-is-up-to-40-smaller-23406>, accessed November 2015
- 'Baldor SmartMotor'. Available at <http://www.baldor.com/Shared/manuals/750-902.pdf>, accessed November 2015
- 'Getting more from the motor'. Available at <http://eandt.theiet.org/magazine/2015/02/efficient-motor-drives.cfm>, accessed November 2015
- 'Grundfos E-pumps'. Available at <https://us.grundfos.com/content/dam/GPU/Literature/LCSE-LFE/LCBSSL04-0614-Grundfos-E-Pump-Brochure.pdf>, accessed November 2015
- 'Rockwell Automation – Kinitex 6000'. Available at http://literature.rockwellautomation.com/idc/groups/literature/documents/td/gmc-td001_en-p.pdf, accessed November 2015
- 'Variable speed motor or geared motor'. Available at http://www.leroy-somer.com/documentation_pdf/3415_en.pdf, accessed November 2015
- 'MOVIMOT® gearmotor with integrated frequency inverter'. Available at <http://www.seweurodrive.com/produkt/movimot-gearmotor-with-integrated-frequency-inverter.htm>, accessed November 2015

- 47 'Lenze smart motor M300'. Available at http://www.lenze.com/fileadmin/lenze/documents/en/catalogue/CAT_MT_MS_13449851_en_GB.pdf, accessed November 2015
- 48 Miller, T.J.: 'Electrical Energy Storage for Vehicles: Targets and Metrics'. Available at <http://www.arpa-e.energy.gov/sites/default/files/documents/files/Ford%20Presentation.pdf>, accessed November 2015
- 49 'Alpha step series'. Available at <http://www.orientalmotor.com/products/stepper-motors/ASX-series-all-in-one-stepper-motor.html>, accessed November 2015
- 50 INMOCO. Available at http://www.inmoco.co.uk/pegasus_integrated_servo_system, accessed November 2015
- 51 'AXOR fastback'. Available at <http://www.motioncontrolproducts.com/pdfs/axor-fast-back-brushless-motor-with-drive.pdf>, accessed November 2015
- 52 Johnson, R.W.: 'A review of high temperature electronics packaging'. Proc. 1989 High Temperature Electronics Conf.
- 53 Olesen, K., Bredtmann, R., Eisele, R.: 'ShowerPower' new cooling concept for automotive applications', *Automot. Power Electron.*, 2006, pp. 1–9
- 54 Hearn, J.A.: 'Future packaging technologies for hybrid electronics in automotive underhood environment'. Proc. 1989 High Temperature Electronics Conf., 1989
- 55 Stolpa, S.: 'Turbulent heat transfer'. Department of Aerospace and Mechanical Engineering, University of Notre Dame, Notre Dame, USA, April 2004
- 56 McClusky, P., Grzybowski, R.R., Das, D., et al.: 'Packaging of electronics for high temperature applications', *Int. J. Microcircuits Electron. Packag.*, 1997, **20**, (3), pp. 409–423
- 57 Mantooth, H.A., Mojarradi, M.M., Johnson, R.W.: 'Emerging capabilities in electronics technologies for extreme environments. Part 1 - High temperature electronics', *IEEE Power Electron. Soc. Newsl.*, 2006, **18**, (1), pp. 9–14
- 58 Şenyıldız, T., Eisele, R., Olesen, K.: 'Thermal management concepts for power electronic modules', Danfoss Silicon Power GmbH, 2003, pp. 1–6
- 59 Liang, Z., Ning, P., Wang, F.: 'Advanced packaging of sic power module for automotive applications'. Energy Conversion Congress and Exposition (ECCE), IEEE, September 2013, p. 2884, 2891 15–19
- 60 Liang, Z., Li, L.: 'HybridPACK2 - advanced cooling concept and package technology for hybrid electric vehicles'. Vehicle Power and Propulsion Conf., VPPC '08. IEEE, September 2008, p. 1, 5, 3–5
- 61 Haque, S., Xing, K., Suchicital, C., et al.: 'Thermal management of high-power electronics modules packaged with interconnected parallel plates'. 14th Annual IEEE Semiconductor Thermal Measurement and Management Symp., SEMI-THERM Proc. 1998, March 1998, p. 111, 119, 10–12
- 62 Yong, W., Guang, Y., Yong-Kyu, Y., et al.: 'Active cooling substrates for thermal management of microelectronics', *IEEE Trans. Compon. Packag. Technol.*, 2005, **28**, (3), pp. 477–483
- 63 Ozpineci, B., Tolbert, L.M., Islam, S.K., et al.: 'Testing, characterization and modelling of SiC diodes for transportation applications'. IEEE Power Electronics Specialists Conf. IEEE. 2002, pp. 1673–1678
- 64 Ghandhi, S.K.: 'Semiconductor power devices' (Wiley, 1977, republished 1998)
- 65 Baliga, B.J.: 'Physics of semiconductor power devices' (JWS Publishing, 1996)
- 66 Shur, M.S., Gaska, R., Khan, A., et al.: 'Wide band gap electronic devices'. Fourth IEEE Int. Caracas Conf. on Devices, Circuits and Systems. IEEE, 2002, pp. 51–58
- 67 O'Connor, J., Smiltens, J.: 'Silicon carbide, a high temperature semiconductor' (Symp. Publications Division, Pergamon Press, New York, 1960)
- 68 Hudgins, J.L., Simin, G.S., Khan, M.A.: 'A new assessment of the use of wide bandgap semiconductors and the potential for GaN'. Power Electronics Specialists Conf., 2002, vol. 4, pp. 1747–1752
- 69 Hornberger, J., Lostetter, A.B., Olejniczak, K.J., et al.: 'Silicon-carbide (SiC) semiconductor power electronics for extreme high-temperature environments'. 4 IEEE Aerospace Conf., Proc., 2004, pp. 2538–2555
- 70 Trivedi, M., Shenai, K.: 'Performance evaluation of high-power wide band-gap semiconductor rectifiers', *J. Appl. Phys.*, 1999, **85**, (9), pp. 6889–6897
- 71 v.Muench, M., Hoeck, P., Pettenpaul, E.: 'IEEE Int. Electron Device Mtg. Technical Digest 337 1977
- 72 Ebert, W., Vescan, A., Borst, T.H., et al.: 'IEEE Intl. Electron Device Mtg. Technical Digest 419 1994
- 73 Shin, M.W., Trew, R.J., Bilbro, G.L.: 'High temperature DC and RF performance of p-type diamond MESFET: comparison with n-type GaAs MESFET', *IEEE Electron Device Lett.*, 1994, **15**, pp. 292–294
- 74 Weitzel, C.E., Palmour, J.W., Carter, C.H., et al.: 'Silicon carbide high power devices', *IEEE Trans. Electron Devices*, 1996, **43**, (10), pp. 1732–1741
- 75 Ozpineci, B., Chinthavali, M.S., Tolbert, L.M.: 'Enhancing power electronic devices with wide band gap semiconductors', *Int. J. High Speed Electron. Syst.*, 2006, **APA**, pp. 545–556
- 76 Ozpineci, B., Tolbert, L.M.: 'Comparison of wide-band gap semiconductors for power electronics applications'. (Department of Energy, United States, 2003)
- 77 Shenai, K., Scott, R.S., Baliga, B.J.: 'Optimum semiconductors for high power electronics', *IEEE Trans. Electron Devices*, 1989, **36**, (9), pp. 1811–182
- 78 Bhalla, A., Chow, T.P.: 'Examination of semiconductors for bipolar power devices', *Inst. Phys. Conf. Ser.*, 1994, **137**, (621), pp. 621–623
- 79 Bhalla, A., Chow, T.P.: 'Bipolar power device performance: dependence on materials, lifetime and device ratings'. Proc. Sixth Int. Symp. on Power Semiconductor Devices and ICs, 1994, pp. 287–292
- 80 Baliga, B.J.: 'Power semiconductor device figure of merit for high frequency applications', *IEEE Electron Device Lett.*, 1989, **10**, (10), pp. 455–457
- 81 Chow, T.P., Tyagi, R.: 'Wide bandgap compound semiconductors for superior high-voltage power devices', *IEEE Trans. Electron Devices*, 1994, **41**, (8), pp. 1481–1483
- 82 Chow, T.P., Khemka, V., Fedison, J., et al.: 'SiC and GaN bipolar power devices', *Solid-State Electron.*, 2000, **44**, (2), pp. 277–301
- 83 Mishra, U.: 'Compound semiconductors; GaN and SiC, separating fact from fiction in both research and business'. Available at http://www.apec-conf.org/wp-content/uploads/2014/01/2_APEC2013Plenary_Compound_Semiconductors_GaN_SiC_Mishra_Transphorm.pdf, accessed 10 April 2015
- 84 Trivedi, M., Shenai, K.: 'High temperature capability of devices on Si and wide bandgap materials'. Industry Applications Conf., IEEE, 1998, vol. 2, pp. 959–962
- 85 Microsemi PPG: 'Gallium nitride (GaN) versus silicon carbide (SiC) In the High Frequency (RF) and power switching applications'. Available at http://www.digikey.co.uk/Web%20Export/Supplier%20Content/Microsemi_278/PDF/Microsemi_GalliumNitride_VS_SiliconCarbide.pdf?redirected=1, accessed 08 April 2015
- 86 Extance, A.: 'SiC and GaN power devices jostle to grow their role', Yole Development, Issue 9, 2013. Available at http://www.yole.fr/iso_upload/mag/powerdev_april2013_ir.pdf 09 Apr, 2015
- 87 Tolbert, L.M., Ozpineci, B., King, T.J., et al.: 'Power electronics for distributed energy systems and transmission and distribution applications', 2005
- 88 Pearton, S.J., Zolper, J.C., Shul, R.J., et al.: 'GaN: processing, defects, and devices', *J. Appl. Phys.*, 1999, **86**, (1), pp. 1–78
- 89 Dang, G.T., Zhang, A.P., Pen, F., et al.: 'High-voltage GaN Schottky rectifiers', *IEEE Trans. Electron Devices*, 2002, **47**, (4), pp. 692–696
- 90 Hudgins, J.L., Simm, G.S., Khan, M.A.: 'A new assessment of the use of wide bandgap semiconductors and the potential of GaN'. The 33d Annual IEEE Power Electronics Specialists Conf. (PESC02), 2002, pp. 1747–1752
- 91 Trivedi, M., Shenai, K.: 'Performance evaluation of high-power wide bandgap semiconductor rectifiers', *Am. Phys. Inst. J. Appl. Phys.*, 1999, **85**, (9), pp. 6889–6897
- 92 Benjia, I., Ruba, M., Szabó, L.: 'Modular electrical machines – a survey'. Proc. of the Int. Scientific Conf. MicroCAD, 2010
- 93 van der Duijn Schouten, N.P., Gordon, B.M., McMahon, R.A., et al.: 'Integrated drives as single-phase motor replacement'. Industry Applications Conf., 1999. Thirty-Fourth IAS Annual Meeting. Conf. Record of the IEEE, 1999, vol. 2, pp. 922–928
- 94 März, M.: 'Technology choices for automotive applications'. Int. Conf. on Automotive Power Electronics (APE), Paris, 2007
- 95 Klumpner, C., Blaabjerg, F., Thogersen, P.: 'Evaluation of the converter topologies suited for integrated motor drives'. 38th IAS Annual Meeting Conf. Record of the Industry Applications Conf., IEEE., 2003, vol. 2, pp. 890–897
- 96 Simon, O., Mahlein, J., Muenzer, M.N., et al.: 'Modern solutions for industrial matrix-converter applications', *IEEE Trans. Ind. Electron.*, 2002, **49**, (2), pp. 401–406
- 97 Pan, M.J., Randall, C.A.: 'A brief introduction to ceramic capacitors', *Electr. Insul. Mag.*, 2010, **26**, (3), pp. 44–50
- 98 Randall, M., Skamsner, D., Kinard, T.: 'Thin film MLCC'. CARTS 2007 Symp. Proc., Albuquerque, NM, 2007, pp. 1–12
- 99 Takamizawa, H., Utsumi, K., Yonezawa, M., et al.: 'Large capacitance multilayer ceramic capacitor', *IEEE Trans. Compon. Hybrids Manuf. Technol.*, 1981, **4**, (4), pp. 345–349
- 100 Yano Research Institute: 'Capacitor market in japan: key research findings 2009' (Yano Research Institute, Tokyo, Japan, 2009)
- 101 Phillips, R., Bultitude, J., Gurav, A., et al.: 'High temperature ceramic capacitors for deep well applications'. CARTS Int. Proc., 2013
- 102 Kim, W., Shin, S.H., Ryu, D.S.: 'Reliability evaluation and failure analysis for high voltage ceramic capacitor', *Adv. Electron. Mater. Packag.*, 2001, pp. 286–195
- 103 Al Ahmar, J., Wiese, S.: 'Fracture mechanics analysis of cracks in multilayer ceramic capacitors'. Electronics System-Integration Technology Conf. (ESTC), 2014, pp. 1–15
- 104 Teverovsky, A.: 'Insulation resistance and leakage currents in low-voltage ceramic capacitors with cracks', *IEEE Trans. Compon. Packag. Manuf. Technol.*, 2014, **4**, (7), pp. 1169–1176
- 105 Kirisken, B., Ugurdag, H.F.: 'Cost-benefit approach to degradation of electrolytic capacitors'. Reliability and Maintainability Symp., 2014, pp. 1–6
- 106 Deshpande, R.P.: 'Capacitors: technology and trends' (Tata McGraw-Hill Education, 2012)
- 107 Bramoulle, M.: 'Electrolytic or film capacitors'. 33rd IAS Annual Meeting Industry Applications Conf., 1998, vol. 2, pp. 1138–1142
- 108 Parler, S.G. Jr.: 'Deriving life multipliers for electrolytic capacitors', *IEEE Power Electron. Soc. Newsl.*, 2004, **16**, pp. 11–12
- 109 Maddula, S.K., Balda, J.C.: 'Lifetime of electrolytic capacitors in regenerative induction motor drives'. Power Electronics Specialists Conf., 2005, pp. 153–159
- 110 Spanik, P., Frivaldsky, M., Kanovsky, A.: 'Life time of the electrolytic capacitors in power applications', *ELEKTRO*, 2014, pp. 233–238
- 111 Sarjeant, W.J., Zirnheld, J., MacDougall, F.W.: 'Capacitors', *IEEE Trans. Plasma Sci.*, 1998, **26**, (5), pp. 1368–1392
- 112 Yaohong, C., Fuchang, L., Hua, L.: 'Study on self-healing and lifetime characteristics of metallized film capacitor under high electric field'. Pulsed Power Conf. (PPC), 2011, pp. 711–716
- 113 'The new high temperature dielectric film for power capacitors', accessed November 2015. Available at http://www.birkelbachfilm.de/pdf/datenblaetter/DTF_Teonex_HV_0912.pdf
- 114 Caliri, L., Bettacchi, P., Boni, E., et al.: 'KEMET film capacitors for high temperature, high voltage and high current'. CARTS Int. Proc.– ECA, 2013
- 115 Klumpner, C., Blaabjerg, F., Thogersen, P.: 'Converter topologies with low passive components usage for the next generation of integrated motor drives'. Power Electronics Specialist Conf., PESC '03. 2003 IEEE 34th Annual, 2, IEEE., pp. 568–573
- 116 Lewandowski, A., Jakobczyk, P., Galinski, M., et al.: 'Self-discharge of electrochemical double layer capacitors', *Phys. Chem. Chem. Phys.*, 2013, **22**, (15), pp. 8692–8699
- 117 Becker, H.I., U.S. pat., 2800.616 to General Electric Co., 1957

- 118 Wang, G., Zhang, L., Zhang, J.: 'A review of electrode materials for electrochemical supercapacitors', *Chem. Soc. Rev.*, 2012, **2**, (41), pp. 797–828
- 119 Burke, A.: 'Power sources', 2000, 91, 37, 2000
- 120 Chen, H., Cong, T.N., Yang, W., *et al.*: 'Progress in electrical energy storage system: a critical review', *Prog. Nat. Sci.*, 2009, **19**, (3), pp. 291–312
- 121 Lambert, S.M., Pickert, V., Holden, J., *et al.*: 'Comparison of supercapacitor and lithium-ion capacitor technologies for power electronics applications'. Fifth IET Int. Conf. on Power Electronics, Machines and Drives (PEMD 2010), April 2010, p. 1.5, 19–21
- 122 Neudeck, P.G., Matus, L.G.: 'An overview of silicon carbide device technology'. Ninth Symp. on Space Nuclear Power Systems, 1992, pp. 12–16
- 123 Casady, J.B., Dillard, W.C., Johnson, R.W., *et al.*: 'A hybrid 6H-SiC temperature sensor operational from 25 C to 500 C', *IEEE Trans. Compon. Packag. Manuf. Technol.*, 1996, **19**, (3), pp. 416–422
- 124 Khazaka, R., Mendizabal, I., Henry, D., *et al.*: 'Survey of high-temperature reliability of power electronics packaging components', *IEEE Trans. Power Electron.*, 2015, **30**, (5), pp. 2456–2464
- 125 Funaki, T., Balda, J.C., Junghans, J., *et al.*: 'Power conversion with SiC devices at extremely high ambient temperatures', *IEEE Trans. Power Electron.*, 2007, **22**, (4), pp. 1321–1329
- 126 Bai, J.G., Yin, J., Zhang, Z., *et al.*: 'High temperature operation of SiC power devices by low-temperature sintered silver die-attachment', *IEEE Trans. Adv. Packag.*, 2007, **30**, (3), pp. 506–510
- 127 Lei, T.G., Calata, J.N., Luo, S., *et al.*: 'Low temperature sintering of nanoscale silver paste for attaching large-area (>100 mm²) chips', *IEEE Trans. Comp. Packag. Technol.*, 2010, **33**, (1), pp. 98–104
- 128 Savrun, E.: 'Packaging considerations for very high temperature microsystems'. Proc. 1st IEEE Sens., 2002, vol. 2, pp. 1139–1143
- 129 Das, M.K., Sumakeris, J.J., Hull, B.A., *et al.*: 'Drift-free, 50 A, 10 kV 4H-SiC pin diodes with improved device yields', *Mater. Sci. Forum*, 2005, **483–485**, pp. 965–968
- 130 ROHM full SiC power Module Data sheet. Available at http://rohmsf.rohm.com/en/products/databook/datasheet/discrete/sic/power_module/bsm180d12p2c101.pdf, accessed 08 April 2015
- 131 Mitsubishi SiC Power modules. Available at http://www.mitsubishielectric.com/semiconductors/catalog/pdf/SiCPowerModules_E_201409.pdf Accessed Apr 08, 2015
- 132 Schupbach, R.M., McPherson, B., McNutt, T., *et al.*: 'High temperature (250°C) SiC power module for military hybrid electrical vehicle applications'. NDIA Ground Veh. Syst. Eng. Technol. Symp., August 2011, pp. 1–7
- 133 Horio, M., Iizuka, Y., Ikeda, Y.: 'Packaging technologies for SiC power modules', *Fuji Electr. Rev.*, 2012, **58**, (2), pp. 75–78
- 134 Chen, Z., Yao, Y., Boroyevich, D., *et al.*: 'A 1200 V, 60 A SiC MOSFET multi-chip phase-leg module for high-temperature, high-frequency applications'. Applied Power Electronics Conf. and Exposition (APEC), 28th Annual IEEE, 2013, pp. 608–615
- 135 Ning, P., Lai, R., Huff, D., *et al.*: 'SiC wirebond multichip phase-leg module packaging design and testing for harsh environment', *IEEE Trans. Power Electron.*, 2010, **25**, (1), pp. 16–23
- 136 Katsis, D., Zheng, Y.: 'Development of an extreme temperature range silicon carbide power module for aerospace applications'. Proc. 39th IEEE Power Electron. Spec. Conf., 2008, pp. 290–294
- 137 Yao, Y., Chen, Z., Lu, G.-Q.: 'Characterization of encapsulants for high-voltage high-temperature power electronic packaging', *IEEE Trans. Compon. Packag. Manuf. Technol.*, 2012, **2**, (4), pp. 539–547
- 138 Yiyang, Y., Guo-Quan, L., Boroyevich, D., *et al.*: 'Survey of high-temperature polymeric encapsulants for power electronics packaging', *IEEE Trans. Compon. Packag. Manuf. Technol.*, 2015, **5**, (2), pp. 168–181
- 139 Kodani, K., Tsukinari, T., Matsumoto, T.: 'New power module concept by forced-air cooling system for power converter'. Int. Power Electronics Conf. (IPEC), June 2010, p. 542, 545, 21–24
- 140 Johnson, R.W., Palmer, M., Wang, C., *et al.*: 'Packaging materials and approaches for high temperature SiC power devices', *Adv. Microelectron.*, 2004, **31**, (1), pp. 8–11
- 141 Mustain, H.A., Lostetter, A.B., Brown, W.D.: 'Evaluation of gold and aluminium wire bond performance for high temperature (500 °C) silicon carbide (SiC) power modules'. Electronic Components and Technology ECTC, 2005, vol. 2, pp. 1623–1628
- 142 Salmon, J.S., Johnson, R.W., Palmer, M.: 'Thick film hybrid packaging techniques for 500°C operation'. Proc. Fourth Int. High Temperature Electronics Conf. (HITEC), 1998, pp. 103–108
- 143 Jian, Y., Zhenxian, L., van Wyk, J.D.: 'High temperature embedded SiC chip module (ECM) for power electronics applications', *IEEE Trans. Power Electron.*, 2007, **22**, (2), pp. 392–398
- 144 Bower, G., Rogan, C.P.E., Kozlowski, J., *et al.*: 'SiC power electronics packaging prognostics'. Aerospace Conf., 2008, pp. 1–12
- 145 Zhenxian, L.: 'Packaging technologies to exploit the attributes of WBG power electronics'. IEEE Workshop on Wide Bandgap Power Devices and Applications (WIPDA), 2014, pp. 1–73
- 146 Pooch, M.H., Dittmer, K.J., Gabisch, D.: 'Investigations on the damage mechanism of aluminium wire bonds used for high power applications'. Proc. European Conf. Electronics Packaging Technology, 1996, pp. 128–131
- 147 Chen, L., Neudeck, P.G.: 'Thick and thin film materials based chip level packaging for high temperature SiC sensors and devices', Technical Report, AYT/NASA Glenn Research Center, 2001
- 148 Cressler, J.D., Mantooh, H.A.: 'Extreme environment electronics' (CRC Press, Florida, 2012)
- 149 Cheng, C.H., siao, H.L., Chu, S.I., *et al.*: 'Low cost silver alloy wire bonding with excellent reliability performance'. 2013 IEEE 63rd Electronic Components and Technology Conf. (ECTC), 28–31 May 2013, vol., no., pp. 1569–1573
- 150 Lu, C.: 'Review on silver wire bonding'. Microsystems, Packaging, Assembly and Circuits Technology Conf. (IMPACT), 2013 Eighth Int., 22–25 October 2013, vol., no., pp. 226–229
- 151 Xiao, Y., Natarajan, R., Chow, T.P., *et al.*: 'Flip-chip flex-circuit packaging for 42 V/16 A integrated power electronics module applications'. 17th Annual IEEE Applied Power Electronics Conf. and Exposition, 2002. APEC 2002. 2002, vol. 1, no., pp. 21–26
- 152 Bai John, G., Lu, G.-Q., Xingsheng, L.: 'Flip-chip on flex integrated power electronics modules for high-density power integration', *IEEE Trans. Adv. Packag.*, 2003, **26**, (1), pp. 54–59
- 153 Muralidharan, G., Tiegs, T.N.: 'Composite die-attach materials for high-temperature packaging applications'. High Temperature Electronics Conf. HITEC, 2006
- 154 Jacob, P., Held, M., Sacco, P., *et al.*: 'Reliability testing and analysis of IGBT power semiconductor modules', IEEE Colloquium IGBT Propulsion Drives, 1995, pp. 4/1–4/5
- 155 Knoerr, M., Kraft, S., Schletz, A.: 'Reliability assessment of sintered nano-silver die attachment for power semiconductors'. Proc. 12th Electron. Package. Technol. Conf., 2010, pp. 56–61
- 156 Buttay, C., Masson, A., Li, J., *et al.*: 'Die attach of power devices using silver sintering bonding process optimization and characterization', *The IMAPS High Temperature Electronics Network.*, 2011, pp. 1–7
- 157 Manikam, V.R., Cheong, K.Y.: 'Die attach materials for high temperature applications: a review', *IEEE Trans. Compon. Packag. Manuf. Technol.*, 2011, **1**, (4), pp. 457–478
- 158 Hopkins, D.C., Kellerman, D.W., Wunderlich, R.A., *et al.*: 'High-temperature, high-density packaging of a 60 kW converter for >200°C embedded operation'. Applied Power Electronics Conf. and Exposition, 2006
- 159 Humpston, G., Jacobson, D.M.: 'Principles of Soldering', ASM International, 2004
- 160 Welch III, W.C., Chae, J., Najafi, K.: 'Transfer of metal MEMS packages using a wafer-level solder transfer technique', *IEEE Trans. Adv. Packag.*, 2005, **28**, (4), pp. 643–649
- 161 Bai, J.G., Zhang, Z.Z., Calata, J.N., *et al.*: 'Low-temperature sintering of nanoscale silver paste: a lead-free die-attach solution for high-performance and high-temperature electronic packaging'. High Temperature Electronics Conf., 2012
- 162 Chih, P.W., Mesa, B.J.A., Hong, X., *et al.*: 'Application and high temperature storage test on Zn-Al-Ge high temperature solder for die attach'. 2014 IEEE 16th Electronics Packaging Technology Conf. (EPTC), 3–5 December 2014, vol., no., pp. 463–468
- 163 McCluskey, F.P., Wang, Z., Dash, M., *et al.*: 'Reliability of high temperature solder alternatives'. High Temperature Electronics Conf. HITEC, 2006
- 164 Lu, G.-Q., Calata, J.N., Zhang, Z., *et al.*: 'A lead-free, low-temperature sintering die-attach technique for high-performance and high temperature packaging'. IEEE CPMT Conf. on High Density Microsystem Design and Packaging and Component Failure Analysis HDP, 2004, pp. 42–46
- 165 Wu, M., Lu, G.-Q., Yin, J., *et al.*: 'Thermal modelling and electrical analysis of the nano-silver paste die-attached power device package at high temperature'. CPES Conf. and Site Visit, 2006
- 166 Joo, S., Baldwin, D.F.: 'Rapid prototyping of micro-systems packaging using a data-driven chip-first process and nano-particles metal colloids', Proc. Electronic Components and Technology, ECTC '05, 2005, vol. 2, pp. 1859–1863
- 167 Parylene Properties. Available at http://scscoatings.com/what_is_parylene/parylene_properties.aspx, accessed 8 April 2015
- 168 Hiromasa, M., Keiichi, E., Satoru, K.: 'Application of silver nano particle to pressureless bonding onto a copper surface – consideration of substitute material for lead solder'. 2014 Eighth Int. Conf. on Integrated Power Systems (CIPS), 25–27 February 2014, vol., no., pp. 1–5
- 169 Cao, X., Wang, T., Ngo, K.D.T., *et al.*: 'Parametric study of joint height for a medium-voltage planar package', *IEEE Trans. Comp. Packag. Technol.*, 2010, **33**, (3), pp. 553–562
- 170 Cao, X., Wang, T., Ngo, K.D.T., *et al.*: 'Height optimization for a medium-voltage planar package'. Proc. 24th Annual IEEE Applied Power Electronics Conf. Exposition, Washington D.C., February 2009, pp. 479–484
- 171 Zhang, Z., Bai, J.G., Lu, G.-Q., *et al.*: 'Low-temperature Sintering Nanoscale Silver Paste as an High-Temperature package Solution'. CPES Conf. and Site Visit, 2005
- 172 Cyclotene* 3000 Series—Processing Procedures for CYCLOTENE 3000 Series Dry Etch Resins. Available at http://msdssearch.dow.com/PublishedLiteratureDOWCOM/dh_08b4/0901b803808b4ed7.pdf?filepath=/888-00006.pdf&fromPage=GetDoc, accessed April 8, 2015
- 173 Cyclotene* 4000 Series—Processing Procedures for CYCLOTENE 4000 Series Resins-DS3000 Immersion Develop Process. Available at http://msdssearch.dow.com/PublishedLiteratureDOWCOM/dh_08b4/0901b803808b4eda.pdf?filepath=/888-00008.pdf&fromPage=GetDoc. Accessed 9 April 2015
- 174 P84 Polyimide Solution—Technical Information. Available at <http://hppyolmer.com/pdfs/P84-%20Polyimide%20Solution1.pdf>, accessed 9 April 2015
- 175 Davis, J.H., Rees, D.W., Riley, I.H.: 'Silicone encapsulating and potting materials'. Proc. IEE-B, Electronics Communication Engineering, 1962, vol. 109, no. 21, pp. 266–270
- 176 Wong, C.P., Segelken, J.M., Balde, J.W.: 'Understanding the use of silicone gels for non-hermetic plastic packaging', *IEEE Trans. Compon., Hybrids Manuf. Technol.*, 1989, **12**, (4), pp. 421–425

- 177 Durapot Epoxies—High Performance Casting, Embedding and Encapsulating Compounds. Available at <http://www.cotronics.com/vo/cotr/pdf/860.pdf>, accessed 8 April 2015
- 178 CF-4721—Technical Data Sheet. Available at <http://nusil.com/products/ProductProfiles/CF-4721/CF-4721P.pdf>, accessed 9 April 2015
- 179 Technical Data Sheet—QSIL 550 2-Part Addition Cure Encapsulant. Available at <http://www.acc-silicones.com/content/products/qsil573.ashx>, accessed 8 April 2015
- 180 EPM-2422—Technical Data Sheet. Available at <http://www.silicone-polymers.com/pdfMaster/EPM-2422P.pdf>, accessed 9 April 2015
- 181 R-2188—Technical Data Sheet. Available at <http://nusil.com/products/ProductProfiles/R-2188/R-2188P.pdf>, accessed 8 April 2015
- 182 Scofield, J.D., Merrett, J.N., Richmond, J., *et al.*: 'Performance and reliability characteristics of 1200 V, 100 A, 200°C half-bridge SiC MOSFET-JBS diode power modules'. Proc. Int. Conf. High Temperature Electron. (HiTEC), Albuquerque, NM, USA, May 2010
- 183 Niwa, K., Nakamura, J., Murakawa, K., *et al.*: 'New alumina substrate for hybrid integrated circuits', *IEEE Trans. Parts Hybrids Packag.*, 1974, **10**, (4), pp. 262–266
- 184 Ji, H., Cheng, X., Chen, H., *et al.*: 'Direct bonding of alumina substrate with copper heat sink in air assisted by ultrasonic vibrations for high power LEDs devices'. 14th Int. Conf. on Electronic Packaging Technology (ICEPT), August 2013, pp. 1158–1161, 11–14
- 185 Chen, L.Y.: 'Temperature dependent dielectric properties of polycrystalline AlN substrates with yttrium oxide additives'. High Temperature Electronics Conf. HITEC 2006, May 2006
- 186 Savrun, E., Wu, D.: 'High-temperature dielectric properties of aluminum nitride'. High Temperature Electronics Conf. HITEC 2006, May 2006
- 187 Mounce, S., McPherson, B., Schupbach, R., *et al.*: 'Ultra-lightweight, high efficiency sic based power electronic converters for extreme environments'. Aerospace Conf., IEEE, 2006, p. 19
- 188 Beica, R.: 'Flip chip market and technology trends'. 2013 European Microelectronics Packaging Conf. (EMPC), September 2013, p. 1, 4, 9–12
- 189 van der Duijn Schouten, N.P., Gordon, B.M., McMahon, R.A., *et al.*: 'Integrated drives using high voltage power ICs'. Eighth Int. Conf. on Power Electronics and Variable Speed Drives, 2000. (IEE Conf. Publ. No. 475), pp. 554–559
- 190 Chou, B., Beilin, S., Jiang, H., *et al.*: 'Multilayer high density flex technology'. Proc. 49th Electronic Components and Technology Conf., 1999.1999, vol., no., pp. 1181–1189
- 191 Chou, B., Beilin, S., Jiang, H., *et al.*: 'Multilayer high density flex technology'. Proc. 49th Electronic Components and Technology Conf., 1999, pp. 1181–1189
- 192 Woo, D.R.M., Hwang, H.Y., Li, J.A.J., *et al.*: 'High power SiC inverter module packaging solutions for junction temperature over 220°C'. IEEE 16th Electronics Packaging Technology Conf. (EPTC), December 2014, p. 31, 35, 3–5
- 193 Pascariu, G., Cronin, P., Crowley, D.: 'Next generation electronics packaging utilizing flip chip technology'. IEEE/CPMT/SEMI 28th Int. Electronics Manufacturing Technology Symp. IEMT 2003. July 2003, pp. 423–4426, 16–18
- 194 Liu, X., Xu, S., Lu, G.-Q., *et al.*: 'Effect of substrate flexibility on solder joint reliability', *Microelectron. Rel.*, 2002, **42**, pp. 1883–1891
- 195 Bivragh, M., Kelley, M., Van Sinte Jans, J.-B., *et al.*: 'Thermo-mechanical modelling and thermal performance characterisation of a 3D folded flex module'. Proc. 56th Electronic Components and Technology Conf., 2006. 30 May 2006–2 June 2006, vol., no., p. 6
- 196 Stockmeier, T., Beckedahl, P., Gobl, C., *et al.*: 'SKiN: Double side sintering technology for new packages'. ISPSD, 2011
- 197 Savrun, E.: 'Packaging considerations for very high temperature Microsystems', *Proc. IEEE*, 2002, **2**, (6), pp. 1139–1143
- 198 Sugawara, Y., Takayama, D., Asano, K.: '3 kV 600 a 4H-SiC high temperature diode module'. Proc. Power Semicond. Devices ICs, 2002, pp. 245–248
- 199 Nawa, K.: 'Reliability study for CTE mismatching in build-up structure'. 51st Proc. Electronic Components and Technology Conf., 2001, pp. 1154–1158
- 200 Chandran, B., Schmidt, W.F., Gordon, M.H.: 'A novel bonding technique to bond CTE mismatched devices'. Proc. Electronic Components and Technology Conf., 46th, May 1996, pp. 1151–1158, 28–31
- 201 Gerber, M., Marz, M.: 'System integration in automotive power systems'. European Conf. on Power Electronics and Applications, September 2005, pp. 10–14
- 202 Jain, P.K.: 'Power electronics for low voltage semiconductor technology: challenges and some possible solutions'. Power Electronics and Motion Control Conf., IPEMC 2004. The 4th International, August 2004, vol. 1, p. 20, 28 14–16
- 203 Kolar, J., Drofenik, U., Biela, J., *et al.*: 'PWM converter power density barriers'. Power Conversion Conf. – Nagoya, April 2007, PCC '07, pp. 2–5